

Package: sitar (via r-universe)

October 9, 2026

Type Package

Title Super Imposition by Translation and Rotation Growth Curve Analysis

Version 1.5.0.9001

Maintainer Tim Cole <tim.cole@ucl.ac.uk>

Description Functions for fitting and plotting SITAR (Super Imposition by Translation And Rotation) growth curve models. SITAR is a shape-invariant model with a regression B-spline mean curve and subject-specific random effects on both the measurement and age scales. The model was first described by Lindstrom (1995) <doi:10.1002/sim.4780141807> and developed as the SITAR method by Cole et al (2010) <doi:10.1093/ije/dyq115>.

License GPL (>= 2)

URL <https://github.com/statist7/sitar>

Depends nlme, R (>= 4.1.0)

Imports dplyr, forcats, ggplot2, glue, graphics, magrittr, methods, purrr, rlang, rsample, splines, splines2, stats, tibble, tidyr

Suggests knitr, rmarkdown

VignetteBuilder knitr

Encoding UTF-8

LazyData yes

LazyLoad yes

RoxygenNote 7.3.2

BugReports <https://github.com/statist7/sitar/issues>

Config/pak/sysreqs libicu-dev

Repository <https://statist7.r-universe.dev>

Date/Publication 2025-07-26 22:38:44 UTC

RemoteUrl <https://github.com/statist7/sitar>

RemoteRef HEAD

RemoteSha c6d70481a4a9b09b8dc32f4d1c28c1a3622aee1e

Contents

sitar-package	3
anova.sitar	5
apv_se	6
berkeley	7
BICadj	8
bupdate	10
cdc2000	10
cLMS	12
codeplot	13
deren	14
dfpower	15
dfset	17
funcall	18
getData.sitar	19
getDV	19
getPeakTrough	21
heights	22
ifun	23
iotf	25
LMS2z	26
LMSfit	28
mplot	29
ob_convertr	30
optimal_design	34
pdLMS	36
plot.sitar	37
plotclean	42
predict.sitar	43
print.sitar	44
print.summary.sitar	45
recalib	46
sitar	47
subsample	50
summary.sitar	51
timegap	52
uk90	54
ukwhopt	55
ukwhoterm	57
velout	58
who06	60
who0607	61
xaxsd	63
xyadj	64
z2cent	65

Index

67

sitar-package	<i>SITAR (SuperImposition by Translation And Rotation) growth curve analysis</i>
---------------	--

Description

SITAR is a method of growth curve analysis, based on **nlme**, that estimates a single mean growth curve as a regression B-spline, plus a set of up to four fixed and random effects (a, b, c and d) (d was added in version 1.2.0) defining how individual growth curves differ from the mean curve. SITAR stands for SuperImposition by Translation And Rotation.

Details

The package also contains some utility functions for the LMS method, as used to construct growth reference centiles (see **gamlss**).

Package:	sitar
Type:	Package
Version:	1.4.0
Date:	2013-09-23
License:	GPL-2

Effect a (or α) measures size, and is a random intercept relative to the spline curve intercept. Effect b (or β) measures timing, the timing of the growth process, and reflects a shift on the x scale relative to the mean. Effect c (or γ) is intensity, and indicates how the x scale is stretched or shrunk reflecting the rate at which 'time' passes for individuals. Effect d (or δ) is a rotation in the plane. The aim is for individual curves, adjusted for abcd to lie on top of (i.e. be superimposed on) the mean curve.

The package creates an object of class **sitar**, based on **nlme**, representing the nonlinear mixed-effects model fit. Generic functions such as `print`, `plot` and `summary` have methods to show the results of the fit, along with `resid`, `coef`, `fitted`, `fixed.effects` and `random.effects` to extract some of its components. The functions `AICadj`, `BICadj` and `varexp` compare respectively the AIC, BIC and variance explained of a series of models, taking into account any transformations of the y variable. Functions `plotclean`, `velout`, `codeplot` and `zapvelout` are useful to clean the data file.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

References

The idea of SITAR growth curve analysis arose from papers by Lindstrom (1995) and Beath (2007) and was first described in Cole et al (2010). The other references describe applications of SITAR to a variety of data forms.

Lindstrom MJ. Self-modelling with random shift and scale parameters and a free-knot spline shape function. *Stat Med* 1995;14:2009-21.

Beath KJ. Infant growth modelling using a shape invariant model with random effects. *Stat Med* 2007;26:2547-64.

Cole TJ, Cortina Borja M, Sandhu J, et al. Nonlinear growth generates age changes in the moments of the frequency distribution: the example of height in puberty. *Biostatistics* 2008;9:159-71.

Cole TJ, Donaldson MD, Ben-Shlomo Y. SITAR—a useful instrument for growth curve analysis. *Int J Epidemiol* 2010;39:1558-66.

Gault EJ, Perry RJ, Cole TJ, et al. Effect of oxandrolone and timing of pubertal induction on final height in Turner’s syndrome: randomised, double blind, placebo controlled trial. *BMJ* 2011;342:d1980.

Johnson L, Llewellyn CH, van Jaarsveld CHM, et al. Genetic and environmental influences on infant growth: prospective analysis of the Gemini twin birth cohort. *PLoS ONE* 2011;6:e19918.

Prentice A, Dibba B, Sawo Y, et al. The effect of prepubertal calcium carbonate supplementation on the age of peak height velocity in Gambian adolescents. *Am J Clin Nutr* 2012;96:1042-50.

Dean MC, Cole TJ. Human life history evolution explains dissociation between the timing of tooth eruption and peak rates of root growth. *PLoS ONE* 2013;8:e54534.

Cole TJ, Statnikov Y, Santhakumaran S, et al. Birth weight and longitudinal growth in infants born below 32 weeks gestation: a UK population study. *Arch Dis Child Fetal Neonatal Ed* 2014;99:F34-F40.

Cole TJ, Rousham EK, Hawley NL, et al. Ethnic and sex differences in skeletal maturation among the Birth to Twenty cohort in South Africa. *Arch Dis Child* 2014;100:138-43.

Cole TJ, Pan H, Butler GE. A mixed effects model to estimate timing and intensity of pubertal growth from height and secondary sexual characteristics. *Ann Hum Biol* 2014;41:7683.

Johnson L, van Jaarsveld CHM, Llewellyn CH, et al. Associations between infant feeding and the size, tempo and velocity of infant weight gain: SITAR analysis of the Gemini twin birth cohort. *Int J Obes* 2014;38:980-7.

Pizzi C, Cole TJ, Richiardi L, et al. Prenatal influences on size, velocity and tempo of infant growth: findings from three contemporary cohorts. *PLoS ONE* 2014;9:e90291.

Ward KA, Cole TJ, Laskey MA, et al. The effect of prepubertal calcium carbonate supplementation on skeletal development in Gambian boys—a 12-year follow-up study. *J C E M* 2014;99:3169-76.

See Also

Useful links:

- <https://github.com/statist7/sitar>
- Report bugs at <https://github.com/statist7/sitar/issues>

anova.sitar*Compare Likelihoods of Fitted SITAR Objects*

Description

anova method for sitar objects, based on anova.lme.

Usage

```
## S3 method for class 'sitar'
anova(
  object,
  ...,
  test = TRUE,
  type = c("sequential", "marginal"),
  adjustSigma = TRUE,
  Terms,
  L,
  verbose = FALSE
)
```

Arguments

object	an object inheriting from class sitar.
...	other optional fitted model objects.
test	an optional logical value controlling whether likelihood ratio tests should be used.
type	an optional character string specifying the type of sum of squares to be used.
adjustSigma	see anova.lme .
Terms	see anova.lme .
L	see anova.lme .
verbose	an optional logical value.

Value

a data frame inheriting from class "anova.lme".

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

apv_se	<i>Bootstrap standard errors for SITAR peak velocity and age at peak velocity</i>
--------	---

Description

apv_se bootstraps a SITAR model to generate standard errors for age at peak velocity (apv) and peak velocity (pv).

Usage

```
apv_se(object, fun = getPeak, nboot = 10, seed = NULL, plot = FALSE, ...)
```

Arguments

object	SITAR model.
fun	function to extract apv and pv from velocity curve (default getPeak), alternative getTakeoff or getTrough.
nboot	number of bootstrap samples (default 10).
seed	integer to initialize the random number generator (default NULL).
plot	logical to control plotting (default FALSE).
...	optional arguments defining the velocity curve to be bootstrapped (plot.sitar arguments xfun, yfun, subset, ns or abc), and graphical par parameters.

Details

If plot is TRUE, the original velocity curve is plotted along with each bootstrap sample's pv versus apv.

Value

a 2x2 array giving the mean and standard error of apv and pv, with attribute "bs" a tibble containing the bootstrap estimates of apv and pv, with NAs removed.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
data(heights)
## fit sitar model for height
model <- sitar(x = age, y = height, id = id, data = heights, df = 4)

## bootstrap standard errors for age at peak velocity and peak velocity
output <- apv_se(model, nboot=3, seed=111, plot=TRUE)
```

berkeley*The Berkeley Child Guidance Study*

Description

The Berkeley Child Guidance Study dataset contains longitudinal anthropometry data for 136 children from birth to 21 years.

Usage

berkeley

Format

A data frame with 4884 observations on the following 10 variables:

id factor with levels 201-278 male and 301-385 female

age years, numeric vector

height cm, numeric vector

weight kg, numeric vector

stem.length cm, numeric vector

bi.acromial cm, numeric vector

bi.ilial cm, numeric vector

leg.circ cm, numeric vector

strength lb, numeric vector

sex factor with level 1 male and level 2 female

Details

The data are for 66 boys and 70 girls from Berkeley, California born in 1928-29 of north European ancestry, and followed from birth to 21 years. Measurements were at ages 0, 0.085, 0.25 to 2 (3-monthly), 2 to 8 (annually), and 8 to 21 (6-monthly) years.

The children were measured for height, weight (undressed), stem length, biacromial diameter, bi-ilial diameter, leg circumference, and dynamometric strength. The data were provided as an appendix to the book by Tuddenham and Snyder (1954), and a few transcription errors are corrected here. A further 19 errors in height and weight as reported in *sitar* issue #7 are also now corrected. The growth dataset in the *fda* package uses heights from the same study.

References

Tuddenham RD, Snyder MM. Physical growth of California boys and girls from birth to eighteen years. University of California Publications in Child Development 1954;1:183-364.

Examples

```
data(berkeley)
## frequencies of age of measurement for each variable
## weight and length/height from birth, other variables from 6-8 years
## few measurements after 18 years
. <- as.factor(berkeley$age)
plot(levels(.), summary(.), type='s', las=1,
      xlab='age of measurement (years)', ylab='frequency of measurements')
points(levels(.), levels(.) < 0, pch=15)
for (i in 3:9) {
  .. <- .[!is.na(berkeley[, names(berkeley)[i]])]
  lines(levels(..), summary(..), type='s', col=i)
}
legend('topright', names(berkeley)[c(3:9)], text.col=c(3:9), bty='n', inset=0.04)
```

BICadj

Ways to compare SITAR models for fit

Description

BICadj and AICadj calculate the BIC and AIC for SITAR models, adjusting the likelihood for Box-Cox transformed y variables. varexp calculates the variance explained by SITAR models, compared to the corresponding fixed effect models. getL is used by [AB]ICadj to find what power the y variable is raised to.

Usage

```
BICadj(..., pattern = NULL)
```

```
AICadj(..., k = 2, pattern = NULL)
```

```
varexp(..., pattern = NULL)
```

```
getL(expr)
```

Arguments

...	one or more SITAR models.
pattern	regular expression defining names of models.
k	numeric, the penalty per parameter to be used; the default k = 2 is the classical AIC.
expr	quoted or unquoted expression containing a single variable name.

Details

The deviance is adjusted if the y variable is power-transformed, using the formula

$$adjusteddeviance = deviance - 2n((\lambda - 1) * \log(gm) + \log(abs(\lambda)))$$

where λ is the power transform, and n and gm are the length and geometric mean of y .

The variance explained is given by

$$\%explained = 100 * (1 - (\sigma_2/\sigma_1)^2)$$

where σ_1 is the fixed effects RSD and σ_2 the SITAR random effects RSD.

BICadj and AICadj accept non-sitar models with a logLik class. varexp ignores objects not of class sitar.

getL does not detect if the variable in expr, or its log, contains a multiplying constant, so that the expressions $\log(x)$ and $1 + 2 * \log(3 * x)$ both return 0.

Value

For BICadj and AICadj a named vector of deviances in increasing order. For varexp a named vector of percentages in decreasing order. For getL the power the variable in expr is raised to, or NA if expr is not a power of (a multiple of) the variable.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[BIC](#), [AIC](#)

Examples

```
data(heights)
## fit sitar model for height
m1 <- sitar(x=age, y=height, id=id, data=heights, df=5)

## update it for log(height)
m2 <- update(m1, y=sqrt(height))

## compare variance explained in the two models
varexp(m1, m2)

## compare BIC adjusting for sqrt transform
## the pattern matches names starting with "m" followed by a digit
BICadj(pattern="^m[0-9]")

## find what power height is raised to
getL(quote(sqrt(sqrt(height))))
```

bupdate	<i>Update the b fixed effect to minimise the b-c random effect correlation</i>
---------	--

Description

A function to update the value of `bstart`, the starting value for the b fixed effect, to minimise the correlation between the random effects b and c.

Usage

```
bupdate(x)
```

Arguments

x a sitar object.

Value

Returns an updated value of the b fixed effect, based on the random effect covariance matrix.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
## fit sitar model with b fixed effect starting value defaulting to 'mean'
m1 <- sitar(x=age, y=height, id=id, data=heights, df=5)
print(fixef(m1)['b'])

## refit with starting value chosen to minimise b-c correlation and df increased
m2 <- update(m1, bstart=bupdate(m1), df=6)
print(fixef(m2)['b'])
```

cdc2000	<i>The CDC 2000 growth reference</i>
---------	--------------------------------------

Description

The CDC growth reference (Kuczmarski et al 2000) for height, weight, body mass index and head circumference, fitted by the LMS method and summarised by values of L, M and S by sex from birth to 19 years.

Usage

```
cdc2000
```

Format

A tibble with 484 observations on the following 14 variables:

years age from 0 to 19 years

L.ht numeric vector

M.ht numeric vector

S.ht numeric vector

L.wt numeric vector

M.wt numeric vector

S.wt numeric vector

L.bmi numeric vector

M.bmi numeric vector

S.bmi numeric vector

L.hc numeric vector

M.hc numeric vector

S.hc numeric vector

sex two-level factor with level 1 male and level 2 female

Details

BMI starts at 2 years, and head circumference stops at 3 years.

The L, M and S values for each measurement correspond respectively to the Box-Cox power, median and coefficient of variation of the distribution by age and sex (Cole & Green 1992). The short names and units for each measurement (see [LMS2z](#)) are as follows: height (ht, cm), weight (wt, kg), body mass index (bmi, kg/m²), head circumference (hc, cm).

References

Cole TJ, Green PJ. Smoothing reference centile curves: the LMS method and penalized likelihood. *Stat Med* 1992;11:1305-19.

Kuczmarski RJ, Ogden CL, Guo SS, Grummer-Strawn LM, Flegal KM, Mei Z, Wei R, Curtin LR, Roche AF, Johnson CL. 2000 CDC growth charts for the United States: methods and development. *Vital Health Stat*, 2002, 11, 246, 1-190.

Examples

```
data(cdc2000)
## calculate 98th centile for weight in girls from birth to 19 years
round(
  setNames(
    LMS2z(x = 0:19, y = 2, sex = 2, measure = 'wt', ref = 'cdc2000',
      toz = FALSE), 0:19), 1)
```

cLMS

*LMS conversion to and from z-scores***Description**

Routines to handle references constructed with the LMS method. Given a set of LMS values, the functions convert z-scores to measurement centiles and vice versa.

Usage

```
cLMS(z, L = 1, M, S)
```

```
zLMS(x, L = 1, M, S)
```

Arguments

z	vector or one-column matrix of z-scores to be converted to measurements.
L	vector of Box-Cox transformation (lambda) values, L in the LMS method.
M	vector of medians (mu), M in the LMS method.
S	vector of coefficients of variation (sigma), S in the LMS method.
x	vector or one-column matrix of measurements to be converted to z-scores.

Details

L, M and S – and if vectors then x and z – should all be the same length, recycled if necessary. The formulae converting x to z and vice versa are:

$$z = \frac{(x/M)^L - 1}{LS}$$

$$x = M(1 + LSz)^{1/L}$$

where L is reset to 10^{-7} if it is zero. The LMS method is the same as the BCCG family in the `gamlss` package, except that lambda in LMS is referred to as nu in BCCG.

Value

If x and z are vectors zLMS and cLMS each return a vector, respectively of z-scores and measurement centiles, with length matching the length of (the longest of) x or z, L, M and S. If x or z are matrices zLMS and cLMS each return a matrix, the number of rows matching the length of (the longest of) L, M and S, and the number of columns matching the length of x or z.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[z2cent](#), [LMS2z](#), [pdLMS](#)

Examples

```
cLMS(z = as.matrix(-2:2), L = 1:-1, M = 5:7, S = rep(0.1, 3))
cLMS(z = 0:2, L = 1:-1, M = 7, S = 0.1)
cLMS(z = as.matrix(0:2), L = 1:-1, M = 7, S = 0.1)
zLMS(x = 6.5, L = 1:-1, M = 5:7, S = rep(0.1, 3))
```

codeplot

*Plot and zap velocity outliers in growth curves***Description**

Handles output from `velout` function to display growth curves with outlying points, either plotting or zapping the outliers.

Usage

```
codeplot(outliers, icode = 4, ..., print = TRUE)
```

```
zapvelout(outliers, icode)
```

Arguments

<code>outliers</code>	Data frame returned from <code>velout</code> .
<code>icode</code>	The code number(s) defining the subset of curves to be displayed or zapped (between 1 and 6).
<code>...</code>	Optional plot parameters.
<code>print</code>	Option to print as well as plot information on each curve.

Details

The function `velout` identifies putative outliers for `y` in data, `codeplot` plots them, and `zapvelout` sets missing those confirmed as outliers. Codes range from 0 (normal) to 8, where 4 and 6 are conventional outliers (see [velout](#)).

Value

`codeplot` returns summary information on each curve with an outlier of the relevant code, and optionally plots the curve. `zapvelout` sets to NA values of `y` whose code is contained in `icode`, and returns the modified data frame.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also[velout](#)**Examples**

```
## identify outliers
outliers <- velout(age, height, id, heights, limit=2)

## plot outliers with code 4 or 6
codeplot(outliers, icode=c(4,6))

## set the 8 outliers missing
newheights <- zapvelout(outliers, icode=6)
```

deren

*Deren prevalence data on child thinness, overweight and obesity***Description**

Age-sex-specific prevalence rates of thinness, overweight and obesity in Ukraine children based on body mass index and IOTF, WHO and CDC cut-offs.

Usage

deren

Format

A tibble with 22 observations on the following 11 variables:

Age postnatal age from 7 to 17 completed years

Sex two-level factor - Boys and Girls

N integer - group sample size

IOTF18.5 thinness prevalence based on IOTF reference and 18.5 cutoff

WHO-2 thinness prevalence based on WHO reference and -2 cutoff

CDC5 thinness prevalence based on CDC reference and 5 cutoff

IOTF25 overweight prevalence based on IOTF reference and 25 cutoff

WHO+1 overweight prevalence based on WHO reference and +1 cutoff

CDC85 overweight prevalence based on CDC reference and 85 cutoff

IOTF30 obesity prevalence based on IOTF reference and 30 cutoff

WHO+2 obesity prevalence based on WHO reference and +2 cutoff

CDC95 obesity prevalence based on CDC reference and 95 cutoff

Details

Note that the overweight prevalences are for overweight excluding obesity, i.e. the prevalence for BMI between the overweight and obesity cutoffs.

Source

The values are obtained from Table 2 of Deren et al (2020), recalculated to full accuracy. <https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0244300>.

References

Deren K, Wyszynska J, Nyankovsky S, Nyankovska O, Yatsula M, Luszczki E, Sobolewski M, Mazur A. 2020. Assessment of body mass index in a pediatric population aged 7-17 from Ukraine according to various international criteria-A cross-sectional study. PLoS ONE 15.

The IOTF reference for children aged 2-18 years is: Cole TJ, Bellizzi MC, Flegal KM, Dietz WH. Establishing a standard definition for child overweight and obesity worldwide: international survey. BMJ 2000; 320: 1240-5. Available at [doi:10.1136/bmj.320.7244.1240](https://doi.org/10.1136/bmj.320.7244.1240)

The WHO reference for children aged 0-5 years is: WHO Child Growth Standards: Length/height-for-age, weight-for-age, weight-for-length, weight-for-height and body mass index-for-age: Methods and development. Geneva: World Health Organization, 2006. Available at: <https://www.who.int/toolkits/child-growth-standards/standards>

The WHO reference for children aged 5-19 years is: de Onis M, Onyango AW, Borghi E, Siyam A, Nishida C, Siekmann J. Development of a WHO growth reference for school-aged children and adolescents. Bulletin of the World Health Organization 2007; 85: 660-7.

The CDC reference for children aged 2-20 years is: Must A, Dallal GE, Dietz WH. Reference data for obesity: 85th and 95th percentiles of body mass index (wt/ht²) and triceps skinfold thickness. American Journal of Clinical Nutrition 1991; 53: 839-46.

Examples

```
## convert IOTF obesity prevalence to WHO obesity prevalence
## and compare with true WHO obesity prevalence - boys and girls age 7-17
data(deren)
ob_convertr(age = Age, sex = Sex, from = 'IOTF 30', to = 'WHO +2',
  pfrom = IOTF30, pto = `WHO+2`, data = deren, plot = 'compare')
```

dfpower

Tabulate BIC of SITAR models by degrees of freedom, fixed effects and xy power transformations

Description

dfpower fits a series of **sitar** models tabulated by combinations of a) specified degrees of freedom for the spline curve, b) specified fixed effects a, b, c, d, c) specified power transformations of x, and d) specified power transformations of y, returning a four-way array of function values (e.g. BIC) applied to each model. The function provides a convenient way to optimise the model.

Usage

```
dfpower(
  object,
  df,
  fixed,
  xpowers,
  ypowers,
  FUN = BICadj,
  maxIter = 50,
  drop = TRUE,
  verbose = FALSE
)
```

Arguments

<code>object</code>	fitted sitar model to be updated.
<code>df</code>	vector of integer spline degrees of freedom to be fitted (defaults to <code>df</code> in <code>object</code>).
<code>fixed</code>	character vector of fixed effects to be included (defaults to <code>fixed</code> in <code>object</code> , typically <code>'a + b + c'</code>).
<code>xpowers</code>	vector of powers to apply to <code>x</code> (defaults to the power of <code>x</code> in <code>object</code>).
<code>ypowers</code>	vector of powers to apply to <code>y</code> (defaults to the power of <code>y</code> in <code>object</code>).
<code>FUN</code>	function to be tabulated (default <code>BICadj</code>).
<code>maxIter</code>	maximum number of iterations per fit (default <code>nlmeControl()\$maxIter</code>).
<code>drop</code>	logical which if <code>TRUE</code> (default) drops redundant dimensions and labels from the returned array.
<code>verbose</code>	logical controlling monitoring, which gives <code>numIter</code> for each model.

Details

`xpowers` and `ypowers` treat power 0 as log. The formula for `x` in `object` must be of the form x^{power} or `fun(x)`, e.g. `x`, `x^0.5` or `log(x)`. More complex formulae e.g. `log(x + 1)` will fail. In this case fit the model with the variable `x1 = x + 1` instead.

`FUN` can be any function returning a single numerical value, e.g. `BICadj`, `BIC`, `AIC`, `varexp` or `sigma`.

Other fixed effects in `object` for covariates in `a.formula`, `b.formula`, `c.formula` or `d.formula` are propagated through all the models. This also applies to the `control` argument if set in `object`.

The run-time can be shortened by reducing `maxIter`, as models often converge quickly or not at all.

Value

Four-way array of returned values, ranked with the largest dimensions first, and by default with single-level dimensions dropped.

Values are returned with changed sign if the model fit generates a warning, or as `NA` if there is an error.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[aperm](#) transposes the returned array; [addmargins](#) adds margins.

Examples

```
data(heights)
m1 <- sitar(x = age, y = height, id = id, data = heights, df = 4)

dfpower(m1, df = 4:6, fixed = c('a', 'a+b', 'a+c', 'a+b+c'),
        xpowers = 0:1, ypowers = 0:1, maxIter = 8)
```

dfset	<i>Find degrees of freedom for a natural spline curve to minimise BIC or AIC</i>
-------	--

Description

dfset fits a natural cubic spline for a range of degrees of freedom, and returns the df minimising the BIC or AIC.

Usage

```
dfset(x, y, data = parent.frame(), FUN = BIC, df = 1:15, plot = FALSE, ...)
```

Arguments

x	vector of x coordinates.
y	vector of y coordinates.
data	environment containing x and y.
FUN	function to be minimised (e.g. BIC or AIC).
df	vector of degrees of freedom to be searched.
plot	logical controlling plotting of FUN versus df.
...	parameters to pass to plot.

Value

degrees of freedom and value of FUN at minimum.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
data(heights)
dfset(age, height, heights, FUN=BIC, plot=TRUE)
dfset(age, height, heights, FUN=function(a) AIC(a, k=1))
```

funcall*Function call with optional inverse*

Description

Applies an expression to vector `v`, optionally inverting the expression first. For example if the expression is `log`, `funcall` returns `log(v)` if `inverse` is `FALSE`, and `exp(v)` if `inverse` is `TRUE`.

Usage

```
funcall(v, vcall, inverse = FALSE)
```

Arguments

<code>v</code>	vector
<code>vcall</code>	expression
<code>inverse</code>	logical

Details

Inverse covers functions `log`, `exp`, `sqrt`, `^`, `*`, `/`, `+`, `-`.

Value

Returns a vector of length `v`.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

getData.sitar	<i>Extract elements of fitted SITAR models</i>
---------------	--

Description

getData, getCovariate and getVarCov methods for sitar objects, based on lme.

Usage

```
## S3 method for class 'sitar'
getData(object)

## S3 method for class 'sitar'
getCovariate(object, ...)

## S3 method for class 'sitar'
getVarCov(obj, ...)
```

Arguments

object, obj an object inheriting from class sitar.
 ... other optional arguments.

Value

Respectively the data frame and x variable used in the fit, and the returned variance-covariance matrix.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

getDV	<i>Extract individual estimates of peak velocity and age at peak velocity</i>
-------	---

Description

getDV takes a point on the mean fitted velocity curve, defined typically as the age at peak velocity or an equivalent landmark age, and maps it onto the corresponding point on individual velocity curves taking into account their timing and intensity.

Usage

```
getDV(object, x = "apv")
```

Arguments

<code>object</code>	a SITAR model.
<code>x</code>	the age of interest, specified either as 'apv', the mean age at peak velocity, or 'ato', the mean age at take-off, or a numerical age.

Details

SITAR is a shape-invariant model, so if there is a turning point on the mean velocity curve, e.g. a peak in puberty, then there will be a corresponding turning point on the velocity curves of all individuals, at an age depending on their timing and intensity. This applies even to individuals who lack measurements at that age, have stopped earlier or started later, so their growth curve is incomplete and lacks the turning point. The returned variable `missing` flags such individuals.

Note that 'D' and 'V' in `getDV` correspond to the plot options for individual Distance and Velocity curves.

Value

A tibble with one row per individual and five columns, where `id`, `age` and `distance` have names corresponding to those used in the SITAR call:

<code>id</code>	subject id.
<code>age</code>	subject's age corresponding to <code>x</code> .
<code>distance</code>	subject's distance at specified age.
<code>velocity</code>	subject's velocity at specified age.
<code>missing</code>	logical where TRUE means subject's specified age lies outside their measurement range.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
data(heights)
library(dplyr)
library(ggplot2)
theme_set(theme_bw())

# fit sitar model
model <- sitar(x = log(age), y = height, id = id, data = heights, df = 5)
(dv <- getDV(model))
(id_missing <- dv %>%
  filter(missing) %>%
  pull(id))

# plot individual velocity curves
ggplot(plot_V(model), aes(age, height, group = id, colour = id)) +
  theme(legend.position = 'inside',
        legend.position.inside = c(0.9, 0.6)) +
```

```

    geom_line() +

    # add individual peak velocities
    geom_point(aes(y = velocity), data = dv) +

    # highlight subjects 2, 7 and 12 with dashed lines
    # despite incomplete curves their peak velocities are estimated
    geom_line(data = . %>% filter(id %in% id_missing), linetype = 2, colour = 'white') +
      geom_point(aes(y = velocity), data = dv %>%
        filter(id %in% id_missing), shape = 1, size = 3)

```

getPeakTrough	<i>Identify peak or trough on curve</i>
---------------	---

Description

Given vectors x and y , returns their values at the peak or trough of the smooth (e.g. cubic spline) curve $y \sim x$.

Usage

```
getPeakTrough(x, y = NULL, peak = TRUE, takeoff = FALSE, Dy = FALSE)
```

```
getPeak(x, y = NULL, peak = TRUE, takeoff = FALSE, Dy = FALSE)
```

```
getTrough(x, y = NULL, peak = FALSE, takeoff = FALSE, Dy = FALSE)
```

```
getTakeoff(x, y = NULL, peak = FALSE, takeoff = TRUE, Dy = FALSE)
```

Arguments

x	vector.
y	vector.
peak	logical determining whether peak or trough is returned.
takeoff	logical determining whether, if peak is FALSE, the trough is takeoff.
Dy	logical if TRUE then y is differentiated first (default FALSE).

Details

Optionally the trough can be specified as takeoff, which is defined for a growth velocity curve as the lowest velocity before the pubertal peak, and if there is no peak then there is by definition no takeoff.

Value

A length-2 vector containing the values of x and y at the peak or trough. If none are identified NA's are returned.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
## create mean height velocity curve
data(heights)
m1 <- sitar(age, height, id, heights, 4)
## plot velocity curve
plot(m1, 'v')
## mark peak, trough and takeoff
xy <- plot_v(m1)
points(t(getPeak(xy)), pch=17)
points(t(getTrough(xy)), pch=25, col=2, bg=2)
points(t(getTakeoff(xy)), pch=25, col=3, bg=3)
```

heights

Serial heights measured in 12 girls

Description

Heights of 12 girls from the Chard Growth Study measured twice a year between 8 and 16 years of age.

Usage

heights

Format

A data frame with 124 observations on the following 4 variables:

id factor of subject ids (levels 1:12).

age vector of ages (years).

height vector of heights (cm).

men vector of ages at menarche (years), where negative values are right censored.

Examples

```
require(graphics)
data(heights)
coplot(height ~ age | id, data = heights, panel=panel.smooth,
       show.given=FALSE, xlab='age (years)', ylab='height (cm)', pch=19)
```

ifun

*Invert an expression defining a data transformation***Description**

Given a transformed variable and the expression used to transform it, ifun creates a function containing the inverse expression that will back-transform the variable.

Usage

```
ifun(expr, verbose = FALSE)
```

Arguments

expr	a single-variable call or quoted expression to be inverted. The variable's name in expr is referred to here as varname.
verbose	a logical controlling printing of the intermediate functions $f(\cdot)$, $g(\cdot)$, $h(\cdot)$ etc (see 'Details').

Details

ifun returns the inverting function such that $\text{ifun}(\text{expr})(\text{eval}(\text{expr})) = \text{varname}$, where expr can include any of the invertible functions in the Math and Ops groups, plus identity and I.

To illustrate its use, consider variants of the sitar model $\text{height} \sim \text{age}$ where age and/or height are transformed, e.g. $\text{height} \sim \log(\text{age})$ or $\log(\text{height}) \sim \sqrt{\text{age}}$. Each model is of the form $y \sim x$ but the units of x and y vary.

The models are compared by plotting the fitted curves in their original units, by first applying suitable functions to back-transform x and y. For example with $\log(\text{age})$, where $\text{expr} = \text{quote}(\log(\text{age}))$, the function $\text{ifun} = \text{function}(x) \exp(x)$ back-transforms $\text{eval}(\text{expr})$ to give age. See the first example.

ifun generalises this process for increasingly complex expr, as the next two examples show.

The final example shows ifun in action with [plot.sitar](#), which uses ifun as the default function for arguments xfun and yfun - they are used to back-transform x and y using the values of expr for x and y extracted from the model's sitar call.

Structuring expr suitably ensures it can be inverted - it should contain a single mention of a single variable (varname here), and possibly functions such as $f(\cdot)$, $g(\cdot)$, $h(\cdot)$ etc such that $\text{expr} = f(g(h(\text{varname})))$. The number of such functions is in principle unlimited. ifun returns $\text{function}(x) h^{-1}(g^{-1}(f^{-1}((x))))$, which ensures that expr is invertible so long as the individual functions are invertible.

Value

The required inverting function, with single argument x. Its "varname" attribute contains varname as a character string.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[plot.sitar](#)

Examples

```
## for best effect run all the code

## define varname variable
(age <- 1:9)

## simple case - age transformed to log(age)
(expr <- quote(log(age)))
## transformed age
eval(expr)
## inverting function, with "varname" attribute set to "age"
ifun(expr)
## inverted transformed age identical to age
all.equal(age, ifun(expr)(eval(expr)))

## more complex case - age transformed to log age since conception
(expr <- quote(log(age + 0.75)))
## inverting function
ifun(expr)
## inverted transformed age identical to age
all.equal(age, ifun(expr)(eval(expr)))

## ludicrously complex case involving exp, log10, ^, pi and trigonometry
(expr <- quote((exp(sin(pi * log10(age + 0.75)/2) - 1)^4)))
## inverting function, showing intermediate stages
ifun(expr, verbose=TRUE)
## identical to original
all.equal(age, ifun(expr)(eval(expr)))

## example of plot.sitar back-transforming transformed x and y in sitar models
## fit sitar models
m1 <- sitar(x=age, y=height^2, id=id, data=heights, df=6)
m2 <- update(m1, x=log(age+0.75), y=height)

## default plot options for xfun & yfun back-transform x & y to original scales
## xfun=ifun(x$call.sitar$x)
## yfun=ifun(x$call.sitar$y)
## compare mean curves for the two models where x & y are on the original scales
plot(m1, 'd', las=1)
lines(m2, 'd', col=2)
```

iotf

*IOTF international body mass index reference***Description**

The IOTF (International Obesity TaskForce) BMI growth reference (Cole and Lobstein 2012), fitted by the LMS method and summarised by values of L, M and S by sex and postnatal age from 2 to 18 years.

Usage

iotf

Format

A tibble with 66 observations on the following 5 variables:

years numeric vector - postnatal age in years

L.bmi numeric vector

M.bmi numeric vector

S.bmi numeric vector

sex two-level factor with level 1 male and level 2 female

Details

The IOTF cutoffs for overweight and obesity (and also thinness) (see Cole et al 2000, 2007) can be obtained from this BMI reference. See the example for how to convert between cutoffs and z-scores.

The L, M and S values for each measurement correspond respectively to the Box-Cox power, median and coefficient of variation of the distribution by age and sex (Cole & Green 1992). The measurement short name and units for [LMS2z](#) are bmi (kg/m2).

Source

The values are tabulated in the Excel spreadsheet IOTF_LMS.xls provided with the Excel add-in LMSGrowth from <https://www.healthforallchildren.com/shop-base/software/lmsgrowth/>

References

Cole TJ, Green PJ. Smoothing reference centile curves: the LMS method and penalized likelihood. Stat Med 1992;11:1305-19.

Cole TJ, Bellizzi MC, Flegal KM, Dietz WH. Establishing a standard definition for child overweight and obesity worldwide: international survey. BMJ 2000;320:1240-3.

Cole TJ, Flegal KM, Nicholls D, Jackson AA. Body mass index cut offs to define thinness in children and adolescents: international survey. BMJ 2007;335:194-7.

Cole TJ, Lobstein T. Extended international (IOTF) body mass index cut-offs for thinness, overweight and obesity. Ped Obes 2012;7:284-94.

Examples

```
data(iotf)
## calculate z-scores by sex corresponding to IOTF cutoffs for thinness,
## overweight and obesity
co <- data.frame(cutoff = c(16, 17, 18.5, 25, 30),
  grade = c('thinness 3', 'thinness 2', 'thinness 1',
    'overweight', 'obesity'))
sexes <- c('boys', 'girls')
with(co,
  cbind(co, lapply(setNames(sexes, sexes), function(x)
    LMS2z(x = 18, y = cutoff, sex = x,
      measure = 'bmi', ref = 'iotf')))))
```

LMS2z

Convert to/from measurement from/to z-score with growth reference

Description

A function to convert between measurements and z-scores using a growth reference previously fitted by the LMS method.

Usage

```
LMS2z(x, y, sex, measure, ref, toz = TRUE, LMStable = FALSE)
```

Arguments

x	vector of ages in units of years.
y	vector or one-column matrix of either measurements or z-scores, depending on the value of toz.
sex	vector where 1/2 = males/females = boys/girls = TRUE/FALSE, based on the uppercased first character of the string.
measure	unique measurement name, as character string, the choice depending on the choice of ref (see e.g. references uk90, who06 and ukwhopt).
ref	unique growth reference, either as name or character string, available as a data object or data frame (e.g. uk90, who06 or ukwhopt).
toz	logical set to TRUE for conversion from measurement to z-score, or FALSE for the reverse.
LMStable	logical set to TRUE to return the associated LMS table as a data frame in attribute LMStable.

Details

Growth references fitted by the LMS method consist of a table of L, M and S values by age and sex. Vectors of L, M and S corresponding to *x* and sex are extracted using cubic interpolation and passed to either [cLMS](#) or [zLMS](#), depending on *toz*.

Disjunct references are supported, where there is a disjunction in the centiles at a particular age. This may be because the measurement changes, e.g. from length to height, or because two different references have been joined together. The disjunction is flagged by including two rows at the common age, but with different L, M and S values, and measurements at this age are ascribed to the older reference. For example the *who06* reference has a disjunction at 2 years reflecting the switch from length to height. As a result height at just below and just above 2 years returns a different z-score.

Value

A vector or matrix containing the transformed values. If *y* is a vector then a vector of `length(x)` is returned, else if *y* is a one-column matrix then a matrix is returned, with `length(x)` rows and `length(y)` columns. The matrix row names are set to *x*, and the column names to either *y* or if *toz* is FALSE, `z2cent(y)`. If *LMStable* is TRUE the associated LMS table is returned as a data frame in attribute *LMStable*.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[z2cent](#). The LMS method can be fitted to data using the package *gamlss* with the BCCG or BCCGo family, where *nu* (originally *lambda*), *mu* and *sigma* correspond to L, M and S respectively.

Examples

```
## convert girls' heights data to UK 90 z-scores
data(heights)
data(uk90)
with(heights, LMS2z(age, height, sex = 2, measure = 'ht', ref = 'uk90'))

## construct table of boys' weight centiles by age for WHO standard
data(who06)
zs <- -4:4*2/3 # z-scores for 9 centiles
ages <- 0:20/4 # 3-month ages to 5 years
LMS2z(ages, as.matrix(zs), sex = 'm', measure = 'wt', ref = 'who06',
      toz = FALSE, LMStable = TRUE)
```

LMSfit

Estimate LMS curves from tabulated growth reference centiles

Description

A function to summarise an existing set of growth reference centiles as the L, M and S curves of the LMS method.

Usage

```
LMSfit(
  x,
  y,
  sex,
  data = parent.frame(),
  centiles = c(3, 10, 25, 50, 75, 90, 97),
  df = c(6, 10, 8),
  L1 = FALSE,
  plot = TRUE,
  ...
)
```

Arguments

x	vector of tabulated ages.
y	matrix of corresponding measurement centiles, e.g. of height or weight, with <code>nrows = length(x)</code> and <code>ncols = length(centiles)</code> .
sex	two-level factor where level 1 corresponds to male and level 2 to female.
data	optional data frame containing x, y and sex.
centiles	vector of centiles corresponding to the columns of y, default <code>c(3, 10, 25, 50, 75, 90, 97)</code> .
df	length-3 vector with the cubic smoothing spline equivalent degrees of freedom (edf) for the L, M and S curves, default <code>c(6, 10, 8)</code> .
L1	logical constraining the L curve to 1, i.e. a Normal distribution, default FALSE.
plot	logical to plot the estimated L, M and S curves, default TRUE.
...	optional graphical parameters for the plots.

Details

At each age the optimal Box-Cox power L_{opt} is estimated to render the centiles closest to Normal, and the corresponding median M_{opt} and coefficient of variation S_{opt} are derived. The three sets of values are then smoothed across age to give L, M and S.

Value

A list with the results:

list("LMS") data frame of sex, x, L, M, S, Lopt, Mopt, Sopt.

list("ey") matrix of predicted values of y.

list("ez") matrix of predicted values of z.

list("fit") matrix of summary statistics for ey, giving for each column cmean the mean centile, zmean the mean z-score, zSD the SD of the z-score, and zmin and zmax the minimum and maximum z-scores.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[LMS2z](#), [z2cent](#). The LMS method can be fitted to data using the package `gamlss` with the BCCG family, where nu (originally lambda), mu and sigma correspond to L, M and S respectively.

Examples

```
## first construct table of boys weight centiles by age for WHO standard
data(who06)
zs <- -4:4*2/3 # z-scores for centiles
ages <- 0:12/4 # ages 0-3 years by 3 months
v <- vapply(as.list(zs), function(z)
  LMS2z(ages, z, sex = 1, measure = 'wt', ref = 'who06', toz = FALSE),
  rep(0, length(ages)))
round(v, 2)

## then back-calculate the original LMS curves and display summary statistics
LMSfit(x=ages, y=v, sex=1, centiles=pnorm(zs)*100, plot=FALSE)
```

mplot

Plot multiple growth curves

Description

Function to plot multiple growth curves indexed by subject id.

Usage

```
mplot(x, y, id, data = parent.frame(), subset = NULL, add = FALSE, ...)
```

Arguments

x	vector of x coordinates.
y	vector of y coordinates.
id	factor denoting subject levels.
data	optional dataframe containing x, y and id.
subset	optional logical defining a subset of rows in data.
add	optional logical defining whether the plot is pre-existing (TRUE) or new (FALSE).
...	Further graphical parameters (see par) may also be supplied as arguments, particularly background colour bg, character expansion cex, colour col, line type lty, line width lwd and character pch.

Details

The arguments x, y and id can be given as character strings. The [par](#) parameters can be functions of vector variables in data, e.g. to colour curves separately by id use: col = id.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
mplot(age, height, id, heights, col=id)
```

ob_converttr	<i>Convert between IOTF, WHO and CDC prevalence rates for child thinness, overweight and obesity</i>
--------------	--

Description

Child thinness, overweight and obesity are defined as the child's body mass index (BMI) lying beyond a pre-specified reference cutoff. Three references are compared: IOTF (International Obesity Task Force), WHO (World Health Organization) and CDC (US Centers for Disease Control and Prevention), each of which have their own cutoffs. ob_converttr takes age-sex-specific prevalence rates of thinness, overweight or obesity based on one of the cutoffs, and converts them to the corresponding rates based on a different cutoff. ob_converttr2 uses paired prevalence rates of overweight and obesity on one cutoff to estimate those based on another cutoff.

Usage

```
ob_converttr(
  age,
  sex,
  from,
  to,
  pfrom = NA,
  pto = NA,
  data = parent.frame(),
  report = c("vector", "wider", "longer"),
  plot = c("no", "density", "compare")
)

ob_converttr2(
  age,
  sex,
  from,
  to,
  pfrom = NA,
  pto = NA,
  data = parent.frame(),
  report = c("vector", "wider", "longer"),
  plot = c("no", "density", "compare")
)
```

Arguments

age	vector of ages between 2 and 18 years corresponding to prevalence rates pfrom.
sex	vector of sexes corresponding to pfrom, coded as either 'boys/girls' or 'male/female' or '1/2' (upper or lower case, based on the first character).
from	name(s) of the BMI cutoff(s) on which the prevalence pfrom is based (see Details).
to	name(s) of the BMI cutoff(s) on which to base the predicted prevalence (see Details).
pfrom	vector of age-sex-specific percentage prevalence rates based on from (ob_converttr) or the names of two or more such prevalence rates (ob_converttr2).
pto	vector (needed for plot = "compare") of known percentage prevalence rates based on to (ob_converttr) or the names of two or more such prevalence rates (ob_converttr2).
data	optional data frame containing age, sex, pfrom and pto.
report	character controlling the format of the returned data: 'vector' for the estimated prevalence rates, 'wider' for the working tibble in wide format, i.e. the from and to data side by side, or 'longer' for the tibble in long format, i.e. two rows per rate, one for from and one for to. For ob_converttr2 the three settings return progressively more information.

`plot` character controlling what if anything is plotted: 'no' for no plot, 'density' to display the BMI density distributions and cutoffs corresponding to `from` and `to`, or 'compare' to display the predicted prevalence rates plotted against the observed rates (`pto`).

Details

The IOTF cutoffs correspond to the value of BMI (kg/m^2) at age 18: IOTF 35 (morbid obesity), IOTF 30 (obesity), IOTF 25 (overweight), IOTF 18.5 (grade 1 thinness), IOTF 17 (grade 2 thinness) and IOTF 16 (grade 3 thinness).

The WHO cutoffs correspond to BMI *z*-scores. Age 5-19 years, WHO +2 (obesity), WHO +1 (overweight) and WHO -2 (thinness). Age 0-5 years, WHO +3 (obesity), WHO +2 (overweight) and WHO -2 (thinness).

The CDC cutoffs correspond to BMI centiles: CDC 95 (obesity), CDC 85 (overweight) and CDC 5 (thinness).

Note: the overweight category needs to be analysed as overweight prevalence plus obesity prevalence, i.e. the prevalence above the overweight cutoff. To predict overweight prevalence excluding obesity prevalence, first calculate predicted overweight prevalence including obesity then subtract predicted obesity prevalence.

The algorithms for `ob_convert` and `ob_convert2` are distinguished by the number of prevalence rates used for the prediction. For `ob_convert` (Cole & Lobstein, 2022) just one rate is used – in this case the algorithm is commutative, meaning that converting a prevalence rate from cutoff A to cutoff B and then from B to A returns the original value. `from` and `to` are the names of the cutoffs, and `pfrom` and optionally `pto` are vectors of percentage prevalence rates.

`ob_convert2` uses two known prevalence rates (Cole & Lobstein, 2023), typically overweight and obesity based on one reference, returning the corresponding rates based on another reference. It is more accurate than `ob_convert` though not exactly commutative. `from` and `to` are the names of the cutoffs as length-2 character strings, while `pfrom` and optionally `pto` are length-2 character strings giving the names of the corresponding vector prevalence rates. For convenience the `from` or `to` names 'CDC', 'IOTF' or 'WHO' expand to the corresponding pairs of cutoffs for overweight and obesity, e.g. 'CDC' expands to `c('CDC 85', 'CDC 95')`.

Alternatively `ob_convert2` can be used to interpolate or extrapolate to one or more specified *z*-score cutoffs assuming the same reference for all cutoffs. Here the values of `from` and `to` are numerical *z*-score cutoffs, with at least two for `from`. See the final example.

The algorithms require the prevalences of obesity and overweight net of obesity to be non-zero, and if they are zero they are set to missing.

Value

The predicted prevalence rates, optionally with a plot visualizing the findings, depending on the `report` and `plot` settings. Each predicted rate is given the name of the relevant cutoff followed by "pred".

With `report` set to "wider" or "longer", extra information is returned reflecting the internal workings of the algorithms. In particular `ob_convert2` returns `b` the regression coefficient of *z*-score prevalence on *z*-score cutoff as described in Cole & Lobstein (2023).

If a plot is selected, the underlying data and plot are returned invisibly with names `data` and `plot`.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

References

Cole TJ, Lobstein T. Exploring an algorithm to harmonize International Obesity Task Force and World Health Organization child overweight and obesity prevalence rates. *Pediatr Obes* 2022;17:e12905. Available at [doi:10.1111/ijpo.12905](https://doi.org/10.1111/ijpo.12905)

Cole TJ, Lobstein T. An improved algorithm to harmonize child overweight and obesity prevalence rates. *Pediatr Obes* 2023;18:e12970. Available at [doi:10.1111/ijpo.12970](https://doi.org/10.1111/ijpo.12970)

The CDC reference for children aged 2-20 years is: Must A, Dallal GE, Dietz WH. Reference data for obesity: 85th and 95th percentiles of body mass index (wt/ht²) and triceps skinfold thickness. *American Journal of Clinical Nutrition* 1991; 53: 839-46.

The IOTF reference for children aged 2-18 years is: Cole TJ, Bellizzi MC, Flegal KM, Dietz WH. Establishing a standard definition for child overweight and obesity worldwide: international survey. *BMJ* 2000; 320: 1240-5. Available at [doi:10.1136/bmj.320.7244.1240](https://doi.org/10.1136/bmj.320.7244.1240)

The WHO reference for children aged 0-5 years is: WHO Child Growth Standards: Length/height-for-age, weight-for-age, weight-for-length, weight-for-height and body mass index-for-age: Methods and development. Geneva: World Health Organization, 2006. Available at: <https://www.who.int/toolkits/child-growth-standards/standards>

The WHO reference for children aged 5-19 years is: de Onis M, Onyango AW, Borghi E, Siyam A, Nishida C, Siekmann J. Development of a WHO growth reference for school-aged children and adolescents. *Bulletin of the World Health Organization* 2007; 85: 660-7.

Examples

```
## convert 10% IOTF overweight prevalence (cutoff IOTF 25, including obesity)
## in 8-year-old boys to overweight prevalence for cutoff WHO +1
ob_convertr(age = 8, sex = 'boys', from = 'IOTF 25', to = 'WHO +1', pfrom = 10)

## compare the BMI density functions and cutoffs for IOTF and WHO
## in 8-year-old boys
ob_convertr2(age = 8, sex = 'boys', from = 'IOTF', to = 'WHO', plot = 'density')

## convert IOTF overweight prevalence to WHO overweight prevalence
## and compare with true value - boys and girls aged 7-17 (22 groups)
## note the need to first add obesity prevalence to overweight prevalence
data(deren)
deren <- within(deren, {
  CDC85 = CDC85 + CDC95
  IOTF25 = IOTF25 + IOTF30
  `WHO+1` = `WHO+1` + `WHO+2`})
ob_convertr(age = Age, sex = Sex, from = 'IOTF 25', to = 'WHO +1',
  pfrom = IOTF25, pto = `WHO+1`, data = deren, plot = 'compare')

## convert IOTF overweight and obesity prevalence to WHO using
## ob_convertr2 - which is more accurate than ob_convertr
ob_convertr2(age = Age, sex = Sex, from = 'IOTF', to = 'WHO',
  pfrom = c('IOTF25', 'IOTF30'), pto = c('WHO+1', 'WHO+2'),
```

```

data = deren, plot = 'compare')

## extrapolate WHO overweight and obesity prevalence (cutoffs +1 and +2)
## to severe obesity prevalence based on cutoffs +2.5 or +3
ob_convertr2(Age, Sex, from = 1:2, to = c(2.5, 3),
  pfrom = c('WHO+1', 'WHO+2'), data = deren, report = 'wider')

```

optimal_design

Optimal design for growth reference centile studies

Description

Two functions for estimating optimal sample size and sample composition when constructing growth reference centiles.

Usage

```
optimal_design(z = -2, lambda = NA, N = NA, SEz = NA, age = 10)
```

```

n_agegp(
  z = -2,
  lambda = NA,
  N = NA,
  SEz = NA,
  minage = 0,
  maxage = 20,
  n_groups = 20
)

```

Arguments

z	z-score on which to base the design, with default -2 which equates to the 2nd centile. If NA, optimal z is calculated from lambda.
lambda	power of age that defines the sample composition. The default NA means calculate optimal lambda from z.
N	total sample size per sex. The default NA means calculate from z or lambda, and SEz if provided.
SEz	target z-score standard error. The default NA means calculate from z or lambda, and N if provided.
age	age at which to calculate SEz. The default 10 returns mean SEz, and if z or lambda are optimal SEz is independent of age.
minage	youngest age (default 0).
maxage	oldest age (default 20).
n_groups	number of age groups (default 20).

Details

Studies to construct growth reference centiles using GAMLSS need to be of optimal size. Cole (SMMR, 2020) has shown that the sample composition, i.e. the age distribution of the measurements, needs to be optimised as well as the sample size. Sample composition is defined in terms of the age power lambda which determines the degree of infant oversampling.

There are two criteria that determine the optimal sample size and sample composition: the centile of interest (as z-score z) and the required level of precision for that centile (as the z-score standard error SEz).

Value

For `optimal_design`, a tibble with columns:

<code>z</code>	as above.
<code>lambda</code>	as above.
<code>N</code>	as above.
<code>SEz</code>	as above.
<code>age</code>	as above.
<code>p</code>	the centile corresponding to z .
<code>plo</code>	lower 95% confidence interval for p .
<code>phi</code>	upper 95% confidence interval for p .

For `n_agegp`, a tibble giving the numbers of measurements to be collected per equal width age group, with columns:

<code>n_varying</code>	numbers for equal width age groups.
<code>age</code>	mean ages for equal width age groups.
<code>n</code>	number for each unequal width age group (only for longitudinal studies).
<code>age_varying</code>	target ages for unequal width age groups (only for longitudinal studies).

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

`gamlss` to fit the centiles with the BCCG, BCT or BCPE family.

Examples

```
## estimate optimal sample composition lambda and precision SEz for 9 centiles
## spaced 2/3 of a z-score apart, based on a sample of 10,000 children

optimal_design(z = -4:4*2/3, N = 10000)

## calculate age group sizes optimised for centiles from the 50th to the 99.6th
## (or equivalently from the 50th to the 0.4th)
```

```
## with a sample of 10,000 children from 0 to 20 years in one-year groups

purrr::map_dfc(0:4*2/3, ~{
  n_agegp(z = .x, N = 10000) %>%
    dplyr::select(!z2cent(.x) := n_varying)
}) %>%
  dplyr::bind_cols(tibble::tibble(age = paste(0:19, 1:20, sep='-')), .)
```

pdLMS	<i>Plot frequency distributions(s) for given L, M and S values in LMS method</i>
-------	--

Description

The LMS method defines frequency distributions in terms of L, M and S parameters. pdLMS plots one or more LMS distributions and optionally returns specified centiles on each distribution.

Usage

```
pdLMS(
  L = 1,
  M = 1,
  S = 0.2,
  zcent = NULL,
  zlim = 3.5,
  N = 1000,
  plot = TRUE,
  ...
)
```

Arguments

L	vector of Box-Cox transformation (lambda) values, L in the LMS method (default 1 corresponding to the Normal distribution).
M	vector of medians (mu), M in the LMS method (default 1).
S	vector of coefficients of variation (sigma), S in the LMS method (default 0.2).
zcent	optional vector of z-scores for conversion to the measurement scale under each distribution.
zlim	scalar defining z-score limits underlying x-axis (default 3.5).
N	number of points per distribution curve (default 1000).
plot	logical for plotting (default TRUE).
...	Further graphical parameters (see par) may also be supplied as arguments, particularly colour col, line type lty, line width lwd and character pch.

Details

L, M and S should all be the same length, recycled if necessary.

Value

An invisible list with the following components:

x	vector of x values for plotting.
density	matrix of densities for each distribution.
centile	matrix of measurement centiles corresponding to zcent under each distribution.

The distributions can be plotted with `matplot(x, density, type='l')`.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[z2cent](#), [LMS2z](#), [cLMS](#)

Examples

```
## plot normal distribution
pdLMS()
## compare variety of distributions
## with centiles corresponding to +3 z-scores
pdLMS(L=-2:3, M=2:3, S=1:3/10, zcent=3, lty=1)
```

plot.sitar

Plot SITAR model

Description

plot and lines methods for objects of class sitar, providing various flavours of plot of the fitted growth curves. Also helper functions to return the data for plotting, e.g. with ggplot2.

Usage

```
## S3 method for class 'sitar'
plot(
  x,
  opt = "dv",
  labels = NULL,
  apv = FALSE,
  xfun = identity,
  yfun = identity,
  subset = NULL,
  ns = 101,
  abc = NULL,
  trim = 0,
```

```

    add = FALSE,
    nlme = FALSE,
    returndata = FALSE,
    ...,
    xlab = NULL,
    ylab = NULL,
    vlab = NULL,
    xlim = c(NA, NA),
    ylim = c(NA, NA),
    vlim = c(NA, NA),
    legend = list(x = "topleft", inset = 0.04, bty = "o")
)

## S3 method for class 'sitar'
lines(x, ...)

plot_d(x, ...)

plot_v(x, ...)

plot_D(x, ...)

plot_V(x, ...)

plot_u(x, ...)

plot_a(x, ...)

plot_c(x, ...)

```

Arguments

<code>x</code>	object of class <code>sitar</code> .
<code>opt</code>	character string containing a subset of letters corresponding to the options: 'd' for fitted Distance curve, 'v' for fitted Velocity curve, 'c' for fitted Crosssectional distance curve, 'D' for individual fitted Distance curves, 'V' for individual fitted Velocity curves, 'u' for Unadjusted individual growth curves, and 'a' for Adjusted individual growth curves. Options 'dvcDV' give spline curves, while 'ua' give data curves made up of line segments. If both distance and velocity curves are specified, the axis for the velocity curve appears on the right side of the plot (y2), and a legend identifying the distance and velocity curves is provided.
<code>labels</code>	optional character vector containing plot labels for x, y and y velocity from the original SITAR model. The three elements can alternatively be provided via parameters <code>xlab</code> , <code>ylab</code> and <code>vlab</code> . The latter take precedence. Default labels are the names of x and y, and "y velocity", suitably adjusted to reflect any back-transformation via <code>xfun</code> and <code>yfun</code> .
<code>apv</code>	optional logical specifying whether or not to calculate the age at peak velocity from the velocity curve. If TRUE, age at peak velocity is calculated as the age

when the second derivative of the fitted curve changes from positive to negative (after applying xfun and/or yfun). Age at peak velocity is marked in the plot with a vertical dotted line, and its value, along with peak velocity, is printed and returned. NB their standard errors can be obtained using the bootstrap with the function apv_se. With plot options 'D' or 'V' values of apv for individual subjects or groups are also returned invisibly.

xfun	optional function to be applied to the x variable prior to plotting (default identity, see Details).
yfun	optional function to be applied to the y variable prior to plotting (default identity, see Details).
subset	optional logical vector of length x defining a subset of data rows to be plotted, for x and data in the original sitar call.
ns	scalar defining the number of points for spline curves (default 101).
abc	vector of named values of random effects a, b, c and d used to define an individual growth curve, e.g. abc = c(a = 1, c = -0.1). Alternatively a single character string defining an id level whose random effect values are used. If abc is set, level is ignored. If abc is NULL (default), or if a, b, c or d values are missing, values of zero are assumed.
trim	number (default 0) of long line segments to be excluded from plot with option 'u' or 'a'. See Details.
add	optional logical defining if the plot is pre-existing (TRUE) or new (FALSE). TRUE is equivalent to using lines.
nlme	optional logical which set TRUE plots the model as an nlme object, using plot.nlme arguments.
returndata	logical defining whether to plot the data (default FALSE) or just return the data for plotting (TRUE). See Value.
...	Further graphical parameters (see par) may also be supplied as arguments, e.g. line type lty, line width lwd, and colour col. For plots involving both distance curves (y1) and velocity curves (y2) the par arguments can be combined (see Details).
xlab	optional label for x axis
ylab	optional label for y axis
vlab	optional label for v axis (velocity)
xlim	optional x axis limits
ylim	optional y axis limits
vlim	optional v axis limits
legend	optional list of arguments for legend with distance-velocity plots, default list(x = 'topleft', inset = 0.04, bty = 'o')

Details

For plots involving both distance curves (options 'dcDua') and velocity curves (options 'vV') the two sets of curves use the y1 and y2 axes respectively and can be annotated differently by combining

their par parameters. For example `col = c(2, 4)` sets the distance curve(s) to red and the velocity curve(s) to blue. (Previously this was done using the named list `y2par`.) To suppress the associated legend set `legend = NULL`.

The transformations `xfun` and `yfun` are applied to the `x` and `y` variables after back-transforming any transformations in the original SITAR call. So for example if `y = log(height)` in the SITAR call, then `yfun` is applied to `height`. Thus the default `yfun = identity` has the effect of back-transforming the SITAR call transformation - this is achieved by setting `yfun = yfun(ifun(x$call.sitar$y))`. For no transformation set `yfun = NULL`. The same applies to `xfun`.

For models that include categorical fixed effects (e.g. a `formula = ~sex + region`) the options `'dv'` provide mean curves for each distinct group. Any continuous (as opposed to grouped) fixed effect variables are set to their mean values in the plots, to ensure that the mean curves are smooth. The resulting plots can be formatted with `par` in the usual way, indexed either by the individual grouping variables (e.g. `sex` or `region` in the example) or the subject factor `id` which indexes all the distinct plots.

The helper functions `plot_d`, `plot_v`, `plot_D`, `plot_V`, `plot_u`, `plot_a` and `plot_c` correspond to the seven plot options defined by their last letter, and return the data for plotting as a tibble, e.g. for use with `ggplot2`. Setting `returndata = TRUE` works similarly but handles multiple options, returning a list of tibbles corresponding to each specified option.

The `trim` option allows unsightly long line segments to be omitted from plots with options `'a'` or `'u'`. It ranks the line segments on the basis of the age gap (`dx`) and the distance of the midpoint of the line from the mean curve (`dy`) using the formula $\text{abs}(dx)/\text{mad}(dx) + \text{abs}(dy)/\text{mad}(dy)$ and omits those with the largest values.

Value

If `returndata` is `FALSE` returns invisibly a list of (up to) three objects:

<code>usr</code>	value of <code>par('usr')</code> for the main plot.
<code>.</code>	
<code>usr2</code>	the value of <code>par('usr')</code> for the velocity (<code>y2</code>) plot.
<code>apv</code>	if argument <code>apv</code> is <code>TRUE</code> a named list giving the age at peak velocity (<code>apv</code>) and peak velocity (<code>pv</code>) from the fitted velocity curve, either overall or (with options <code>D</code> or <code>V</code> , invisibly) for all subjects.

If `returndata` is `TRUE` (which it is with the helper functions) returns invisibly either a tibble or named list of tibbles, containing the data to be plotted. The helper functions each return a tibble where the first three variables are named according to `x`, `y` and `id` from the original sitar call, plus variable `'groups'` and the relevant categorical variables for grouped curves. Note that `x` and `y` are returned after applying `xfun` and `yfun`. Hence if for example `x = log(age)` in the SITAR call then `x` as returned corresponds by default to `age`.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[mplot](#), [plotclean](#), [ifun](#), [apv_se](#)

Examples

```
## fit sitar model
m1 <- sitar(x = age, y = height, id = id, data = heights, df = 4)

## draw fitted distance and velocity curves
## with distance in red and velocity in blue
## marking age at peak velocity (apv)
plot(m1, col = c('red', 'blue'), apv = TRUE)

## bootstrap standard errors for apv and pv
## Not run:
res <- apv_se(m1, nboot = 20, plot = TRUE)

## End(Not run)
## draw individually coloured growth curves adjusted for random effects
## using same x-axis limits as for previous plot
plot(m1, opt = 'a', col = id, xlim = xaxsd())

## add mean curve in red
lines(m1, opt = 'd', col = 'red', lwd = 2)

## add curve for an individual with random effects a, b and c = -1 SD
lines(m1, opt = 'd', lwd = 2, abc = -sqrt(diag(getVarCov(m1))))

## compare curves for early versus late menarche
heights <- within(sitar::heights, {
  men <- abs(men)
  late <- factor(men > median(men))
})
## fit model where size and timing differ by early vs late menarche
m2 <- sitar(log(age), height, id, heights, 5,
  a.formula = ~late, b.formula = ~late)
## plot distance and velocity curves for the two groups
plot(m2, opt = 'dv', lwd = 2, col = late)
legend('bottom', paste(c('early', 'late'), 'menarche'),
  lwd = 2, col = 1:2, inset = 0.04)
## alternatively plot early and late groups separately
## early
lines(m2, opt = 'dv', subset = late == FALSE, col = 'white')
## late
lines(m2, opt = 'dv', subset = late == TRUE, col = 'white')

## draw fitted height distance curves coloured by subject, using ggplot
## Not run:
require(ggplot2)
ggplot(plot_D(m1), aes(age, height, colour = .id)) +
  geom_line(show.legend = FALSE)

## End(Not run)
```

plotclean

Plot multiple growth curves to identify outliers

Description

A version of `mplot` to plot growth curves and identify outliers. When outliers are clicked on, and if `id` is specified, the corresponding growth curve is highlighted. If `id` is not specified the selected point is highlighted. Use right-click to exit.

Usage

```
plotclean(
  x,
  y,
  id = NULL,
  data = parent.frame(),
  n = length(x),
  par.out = list(pch = 20),
  ...
)
```

Arguments

<code>x</code>	vector of x coordinates.
<code>y</code>	vector of y coordinates.
<code>id</code>	factor of subject levels indexing each growth curve.
<code>data</code>	optional dataframe containing x, y and id.
<code>n</code>	maximum number of points to be identified.
<code>par.out</code>	list of optional graphical parameters to control appearance of selected outlying points and lines.
<code>...</code>	Further graphical parameters (see par) may also be supplied as arguments for lines and points, particularly line type, lty, line width, lwd and color, col.

Value

`plotclean` returns either a vector rows (if data is not specified) or a list:

<code>rows</code>	a vector of row numbers corresponding to the selected points.
<code>data</code>	a subset of data consisting of rows <code>rows</code> , and columns <code>id</code> , <code>x</code> and <code>y</code> .

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
if (interactive()) plotclean(age, height, id, heights)
```

predict.sitar

*Predict SITAR model***Description**

Predict method for sitar objects, based on predict.lme.

Usage

```
## S3 method for class 'sitar'
predict(
  object,
  newdata = getData(object),
  level = 1L,
  ...,
  deriv = 0L,
  abc = NULL
)
```

Arguments

object	an object inheriting from class sitar.
newdata	an optional data frame to be used for obtaining the predictions, defaulting to the data used to fit object. It requires named columns for x, and also for id if level = 1, matching the names in object. Variables with the reserved names x = .x or id = .id take precedence over the model x and id variables. Any covariates in a.formula, b.formula, c.formula or d.formula can also be included. By default their values are set to the mean, so when level = 0 the prediction represents the mean curve.
level	an optional integer vector giving the level(s) of grouping to be used in obtaining the predictions, level 0 corresponding to the population predictions. Defaults to level 1, and level = 0:1 fits both levels.
...	other optional arguments: asList, na.action and naPattern.
deriv	an optional integer specifying predictions corresponding to the fitted curve and/or its derivative. deriv = 0 (default) specifies the distance curve, deriv = 1 the velocity curve and deriv = 0:1 fits both.
abc	an optional named vector containing values of a subset of a, b, c and d, default NULL. Ignored if level = 0. It gives predictions for a single subject with the specified values of a, b, c and d, where missing values are set to 0. Alternatively abc can contain the value for a single id.

Details

If x and/or y include transformations, e.g. $x = \log(\text{age})$, predictions are returned in the original units by back-transforming x and/or y appropriately using the function `ifun`.

Value

A vector of the predictions, or a list of vectors if `asList = TRUE` and `level == 1`, or a data frame if `length(level) * length(deriv) > 1`. The data frame column names are (a subset of): `(id, predict.fixed, predict.id, vel.predict.fixed, vel.predict.id)`.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
data(heights)
require(dplyr)
require(tidyr)
require(ggplot2)
## fit model
m1 <- sitar(x = age, y = height, id = id, data = heights, df = 5)
df <- data.frame(age = 9:16, id = 5)

## height predictions at level 0
predict(m1, newdata = df, level = 0)

## height predictions at level 1 for subject 5
predict(m1, newdata = df, level = 1)

## velocity predictions for subjects with early, average and late puberty
m2 <- sitar(x = log(age), y = height, id = id, data = heights, df = 5)
tibble(age = 80:160/10) %>%
  mutate(early = predict(m2, ., deriv = 1, abc = c(b = -0.07)),
         average = predict(m2, ., deriv = 1, level = 0),
         late = predict(m2, ., deriv = 1, abc = c(b = 0.07))) %>%
  pivot_longer(early:late, names_to = 'group', values_to = 'height_velocity') %>%
  ggplot(aes(age, height_velocity, group = group, colour = group)) +
  geom_path(show.legend = FALSE)
```

`print.sitar`

Print SITAR model

Description

Print method for `sitar` objects, based on `print.lme`.

Usage

```
## S3 method for class 'sitar'
print(x, ...)
```

Arguments

x an object inheriting class sitar.
... other optional arguments.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

`print.summary.sitar` *Print summary of SITAR model*

Description

A `print.summary` method for `sitar` objects.

Usage

```
## S3 method for class 'summary.sitar'
print(x, verbose = FALSE, ...)
```

Arguments

x an object inheriting from class `summary.sitar`.
verbose a logical to control the amount of output.
... to specify extra arguments.

Value

A formatted summary of the object.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

recalib

Recalibrate x, y data using SITAR random effects

Description

A function to recalibrate x,y data using SITAR random effects

Usage

```
recalib(xc, yc, id = NULL, data, xcnew = NULL, ycnew = NULL, model, from, to)
```

Arguments

xc	character vector defining column name(s) of x data to be recalibrated.
yc	character vector defining column name(s) of y data to be recalibrated.
id	factor defining from and to rows. If NULL then recalibrate all rows.
data	dataframe containing xc, yc and id.
xcnew	column names for replacement columns xc. If default NULL then use names xcnew1... .
ycnew	column names for replacement columns yc. If default NULL then use names ycnew1... .
model	sitar model defining the random effects to be used for recalibration.
from	level of id defining existing data (must be a single row in coef{model}).
to	level of id defining data to be recalibrated (a single row in coef{model}).

Details

recalib recalibrates the values of xc and yc based on model. xc values are changed to:

$$(xc - c(\text{coef}[\text{from}, 'b'])) * \exp(\text{coef}[\text{from}, 'c'] - \text{coef}[\text{to}, 'c']) + \text{coef}[\text{to}, 'b'].$$

yc values are changed to: $yc - \text{coef}[\text{from}, 'a'] + \text{coef}[\text{to}, 'a'].$

Value

Returns the dataframe data with the from rows of xc and yc recalibrated.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

sitar

Fit SITAR growth curve model

Description

SITAR is a method of growth curve analysis, based on **nlme**, that summarises a set of growth curves with a mean growth curve as a regression spline, plus a set of up to four fixed and random effects (a, b, c and d) defining how individual growth curves differ from the mean curve.

Usage

```
sitar(  
  x,  
  y,  
  id,  
  data,  
  df,  
  knots,  
  fixed = NULL,  
  random = "a + b + c",  
  pdDiag = FALSE,  
  a.formula = ~1,  
  b.formula = ~1,  
  c.formula = ~1,  
  d.formula = ~1,  
  d.adjusted = FALSE,  
  stype = c("nsk", "ns"),  
  bounds = 0.04,  
  start,  
  xoffset = "mean",  
  bstart = xoffset,  
  returndata = FALSE,  
  verbose = FALSE,  
  correlation = NULL,  
  weights = NULL,  
  subset = NULL,  
  method = "ML",  
  na.action = na.fail,  
  control = nlmeControl(msMaxIter = 100, returnObject = TRUE),  
  keep.data = TRUE  
)  
  
## S3 method for class 'sitar'  
update(object, ..., evaluate = TRUE)
```

Arguments

x vector of ages.

<code>y</code>	vector of measurements.
<code>id</code>	factor of subject identifiers.
<code>data</code>	data frame containing variables <code>x</code> , <code>y</code> and <code>id</code> .
<code>df</code>	degrees of freedom for cubic regression spline (0 or more, see Details).
<code>knots</code>	vector of values for knots (default <code>df</code> quantiles of <code>x</code> distribution).
<code>fixed</code>	character string specifying <code>a</code> , <code>b</code> , <code>c</code> , <code>d</code> fixed effects (default random or the subset of " <code>a + b + c + d</code> " within random).
<code>random</code>	character string specifying <code>a</code> , <code>b</code> , <code>c</code> , <code>d</code> random effects (default " <code>a+b+c</code> "). Alternatively <code>nlme</code> formula e.g. " <code>list(id = pdDiag(a + b + c ~ 1))</code> ".
<code>pdDiag</code>	logical which if TRUE fits a diagonal random effects covariance matrix, or if FALSE (default) a general covariance matrix.
<code>a.formula</code>	formula for fixed effect <code>a</code> (default <code>~ 1</code>).
<code>b.formula</code>	formula for fixed effect <code>b</code> (default <code>~ 1</code>).
<code>c.formula</code>	formula for fixed effect <code>c</code> (default <code>~ 1</code>).
<code>d.formula</code>	formula for fixed effect <code>d</code> (default <code>~ 1</code>).
<code>d.adjusted</code>	logical defining <code>x</code> scale for random effect <code>d</code> (default FALSE means <code>x</code> unadjusted, TRUE means <code>x</code> adjusted with random effects <code>b</code> and <code>c</code>).
<code>stype</code>	version of natural spline curve to be fitted, default " <code>nsk</code> " or " <code>ns</code> ". See Details.
<code>bounds</code>	span of <code>x</code> for regression spline, or fractional extension of range (default 0.04).
<code>start</code>	optional numeric vector of initial estimates for the fixed effects, or list of initial estimates for the fixed and random effects (see nlme).
<code>xoffset</code>	optional value of offset for <code>x</code> (either " <code>mean</code> " (default), " <code>apv</code> " or value).
<code>bstart</code>	optional starting value for fixed effect <code>b</code> (either " <code>mean</code> ", " <code>apv</code> " or value (default <code>xoffset</code>)).
<code>returndata</code>	logical which if TRUE causes the model matrix to be returned, or if FALSE (default) the fitted model. Setting <code>returndata</code> TRUE is useful in conjunction with subset and subsample for simulation purposes.
<code>verbose</code>	optional logical value to print information on the evolution of the iterative algorithm (see nlme).
<code>correlation</code>	optional <code>corStruct</code> object describing the within-group correlation structure (see nlme).
<code>weights</code>	optional <code>varFunc</code> object or one-sided formula describing the within-group heteroscedasticity structure (see nlme).
<code>subset</code>	optional expression indicating the subset of the rows of data that should be used in the fit (see nlme).
<code>method</code>	character string, either " <code>REML</code> " or " <code>ML</code> " (default) (see nlme).
<code>na.action</code>	function for when the data contain NAs (see nlme).
<code>control</code>	list of control values for the estimation algorithm (see nlme) (default <code>nlmeControl(returnObject = TRUE)</code>).
<code>keep.data</code>	logical to control saving data as part of the model object (default TRUE).

object	object of class <code>sitar</code> .
...	further parameters for <code>update</code> consisting of any of the above <code>sitar</code> parameters.
evaluate	logical to control evaluation. If <code>TRUE</code> (default) the expanded <code>update</code> call is passed to <code>sitar</code> for evaluation, while if <code>FALSE</code> the expanded call itself is returned.

Details

The SITAR model usually has up to three random effects (a, b and c), termed size, timing and intensity respectively. `df` sets the degrees of freedom for the mean spline curve, taking values from 1 (i.e. linear) upwards. In addition there is a random effect for the slope, d, which is fitted when `df = 0`, and combined with a, it provides the classic random intercept random slope model, which is similar to the 1 df spline model. In addition d can be fitted, along with a, b and c, to extend SITAR to model variability in the adult slope of the growth curve.

`xoffset` allows the origin of x to be varied, while `bstart` specifies the starting value for b, both of which can affect the model fit and particularly b. The values of `bstart`, `knots` and `bounds` are offset by `xoffset` for fitting purposes, and similarly for fixed effect b.

The formulae `a.formula`, `b.formula`, `c.formula` and `d.formula` allow for `cov.names` and can include functions and interactions. `make.names` is used to ensure that the names of the corresponding model terms are valid. The modified names, not the original names, need to be specified in `predict.sitar`.

`update` updates the model by taking the object call, adding any new parameters and replacing changed ones. Where feasible the fixed and random effects of the model being updated are suitably modified and passed via the `start` argument.

The mean curve is a natural cubic spline, fitted originally with `splines::ns` but now by default with `splines2::nsk`, where the choice is set by `stype`. Both give the same mean curve, but `nsk` is faster than `ns` and its fixed effect coefficients have a direct interpretation: added to fixed effect a they give the values of the mean curve at the `df` right-most knots, while a is the value at the left-most knot. The knots themselves depend on fixed effects b and c (where fitted) and are accessed via `attr(object, "knots")`.

Value

An object inheriting from class `sitar` representing the nonlinear mixed-effects model fit, with all the components returned by `nlme` (see [nlmeObject](#) for a full description) plus the following components:

<code>fitnlme</code>	the function returning the predicted value of y.
<code>data</code>	copy of data (if <code>keep.data</code> true).
<code>constants</code>	data frame of mean a-b-c-d values for unique combinations of covariates (excluding x).
<code>call.sitar</code>	the internal <code>sitar</code> call that produced the object.
<code>xoffset</code>	the value of <code>xoffset</code> .
<code>ns</code>	the <code>lm</code> object providing starting values for the B-spline curve.

In addition attributes `stype` and `knots` are set.

Generic functions such as `print`, `plot`, `anova` and `summary` have methods to show the results of the fit. The functions `residuals`, `coef`, `fitted`, `fixed.effects`, `random.effects`, `predict`, `getData`, `getGroups`, `getCovariate` and `getVarCov` can be used to extract some of its components.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
data(heights)
## fit simple model
(m1 <- sitar(x=age, y=height, id=id, data=heights, df=5))

## relate random effects to age at menarche (with censored values +ve)
## both a (size) and b (timing) are positively associated with age at menarche
(m2 <- update(m1, a.formula = ~abs(men), b.formula = ~abs(men), c.formula = ~abs(men)))
```

subsample

Sample from SITAR dataset

Description

A function to sample from a SITAR dataset for experimental design purposes. Two different sampling schemes are offered, based on the values of `id` and `x`.

Usage

```
subsample(x, id, data, prob = 1, xlim = NULL)
```

Arguments

<code>x</code>	vector of age.
<code>id</code>	factor of subject identifiers.
<code>data</code>	dataframe containing <code>x</code> and <code>id</code> .
<code>prob</code>	scalar defining sampling probability. See Details.
<code>xlim</code>	length 2 vector defining range of <code>x</code> to be selected. See Details.

Details

With the first sampling scheme `xlim` is set to `NULL` (default), and rows of data are sampled with probability `prob` without replacement. With the second sampling scheme `xlim` is set to a range within `range(x)`. Subjects `id` are then sampled with probability `prob` without replacement, and all their rows where `x` is within `xlim` are selected. The second scheme is useful for testing the power of the model to predict later growth when data only up to a certain age are available. Setting `xlim` to `range(x)` allows data to be sampled by subject. The returned value can be used as the `subset` argument in `sitar` or `update.sitar`.

Value

Returns a logical the length of x where TRUE indicates a sampled value.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[sitar](#)

Examples

```
## draw 50% random sample
s50 <- subsample(age, id, heights, prob=0.5)

## truncate age range to 7-12 for 50% of subjects
t50 <- subsample(age, id, heights, prob=0.5, xlim=c(7, 12))
```

summary.sitar

Create summary of SITAR model

Description

A summary method for sitar objects based on [summary.lme](#).

Usage

```
## S3 method for class 'sitar'
summary(object, adjustSigma = TRUE, verbose = FALSE, ...)
```

Arguments

object	object inheriting from class sitar.
adjustSigma	optional logical (see summary.lme).
verbose	optional logical to control the amount of output in print.summary.sitar.
...	some methods for this generic require additional arguments. None are used in this method.

Value

an object inheriting from class `summary.sitar` with all components included in object (see [lmeObject](#) for a full description of the components) plus the components for [summary.lme](#) and the following components:

<code>x.adj</code>	vector of length <code>x</code> in object with <code>x</code> values adjusted for subject-specific random effects <code>b</code> and <code>c</code> .
<code>y.adj</code>	vector of length <code>y</code> in object with <code>y</code> values adjusted for subject-specific random effects <code>a</code> .
<code>apv</code>	length 2 vector giving respectively age at peak velocity and peak velocity based on the fitted distance curve (using transformed <code>x</code> and <code>y</code> where specified).

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

<code>timegap</code>	<i>Select equally spaced ages from a vector of ages</i>
----------------------	---

Description

`timegap` indexes elements in a vector of ages such that the indexed ages are spaced integer multiples of a time interval apart, to within a given tolerance. `timegap.id` is a wrapper to apply `timegap` within levels of factor `id`. The selected ages can then be split into age groups the specified time interval wide, ensuring that (virtually) every subject has at most one measurement per interval.

Usage

```
timegap(age, gap, tol = 0.1 * gap, multiple = FALSE)
```

```
timegap.id(
  age,
  id,
  data = parent.frame(),
  gap,
  tol = 0.1 * gap,
  multiple = FALSE
)
```

```
diffid(
  age,
  id,
  data = parent.frame(),
  lag = 1,
  differences = 1,
  sort = FALSE,
  keepNA = FALSE
)
```

Arguments

age	vector of ages.
gap	numeric, the required positive time gap between selected ages.
tol	numeric, the positive tolerance around the gap (default $0.1 * \text{gap}$).
multiple	logical, whether or not to return multiple solutions when found (default FALSE).
id	factor of subject ids.
data	data frame optionally containing age and id.
lag	an integer indicating which lag to use.
differences	an integer indicating the order of the difference.
sort	a logical indicating whether to first sort by id and age.
keepNA	a logical indicating whether to keep generated NAs.

Details

timegap calculates all possible differences between pairs of ages, expresses them as integer multiples of gap, restricts them to those within tolerance and identifies those providing the longest sequences. For sequences of the same length, those with the smallest standard deviation of successive differences (modulo the time interval) are selected.

Value

With timegap, for unique solutions, or multiple solutions with multiple FALSE, a vector of indices named with age. With timegap.id the subject vectors are returned invisibly, concatenated.

With multiple TRUE, where there are multiple solutions they are returned as a named matrix.

diffid returns diff(age) applied within id. With keepNA TRUE a suitable number of NAs are added at the end, while if FALSE all NAs are omitted.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
data(heights)

## bin age into 1-year groups by id
## gives multiple measurements per id per year
with(heights, table(floor(age), id))

## now select heights measured multiples of 1 year apart
(tg1 <- timegap.id(age, id, heights, 1))

## no more than one measurement per id per year
with(heights[tg1, ], table(floor(age), id))

## most time intervals close to 1 year
summary(diffid(age, id, heights[tg1, ], lag=1))
```

uk90

*UK 1990 growth reference***Description**

The UK 1990 growth reference (Freeman et al 1995, Cole et al 1998) for height, weight, body mass index, circumferences and percent body fat, fitted by the LMS method and summarised by values of L, M and S by sex from 23 weeks gestation to 23 years.

Usage

uk90

Format

A tibble with 588 observations on the following 26 variables:

years numeric vector
L.ht numeric vector
M.ht numeric vector
S.ht numeric vector
L.wt numeric vector
M.wt numeric vector
S.wt numeric vector
L.bmi numeric vector
M.bmi numeric vector
S.bmi numeric vector
L.head numeric vector
M.head numeric vector
S.head numeric vector
L.sitht numeric vector
M.sitht numeric vector
S.sitht numeric vector
L.leglen numeric vector
M.leglen numeric vector
S.leglen numeric vector
L.waist numeric vector
M.waist numeric vector
S.waist numeric vector
L.bfat numeric vector
M.bfat numeric vector
S.bfat numeric vector
sex two-level factor with level 1 male and level 2 female

Details

The L, M and S values for each measurement correspond respectively to the Box-Cox power, median and coefficient of variation of the distribution by age and sex (Cole & Green 1992). The short names and units for each measurement (see [LMS2z](#)) are as follows: height (ht, cm), weight (wt, kg), body mass index (bmi, kg/m²), head circumference (head, cm), sitting height (sitht, cm), leg length (leglen, cm), waist circumference (waist, cm) and percent body fat (fat,

Source

The values are tabulated in the spreadsheet British1990.xls provided with the Excel add-in LMS-growth from: <https://www.healthforallchildren.com/shop-base/software/lmsgrowth/>

References

Cole TJ, Green PJ. Smoothing reference centile curves: the LMS method and penalized likelihood. Stat Med 1992;11:1305-19.

Cole TJ, Freeman JV, Preece MA. British 1990 growth reference centiles for weight, height, body mass index and head circumference fitted by maximum penalized likelihood. Stat Med 1998;17:407-29.

Freeman JV, Cole TJ, Chinn S, et al. Cross sectional stature and weight reference curves for the UK, 1990. Arch Dis Child 1995;73:17-24.

Examples

```
data(uk90)
## calculate median BMI in girls from birth to 10 years
LMS2z(x = 0:10, y = 0, sex = 2, measure = 'bmi', ref = 'uk90', toz = FALSE)
```

ukwhopt

UK-WHO growth reference including preterm

Description

The UK-WHO growth reference for height, weight, BMI and head circumference (see Wright et al 2010), fitted by the LMS method and summarised by values of L, M and S by sex from 26 weeks gestation to 20 years.

Usage

```
ukwhopt
```

Format

A tibble with 542 observations on the following 17 variables:

age_wm numeric vector - age in weeks or months - see **wm**

wm three-level factor indicating weeks or months: **wkga** = gestational weeks, **wk** = postnatal weeks, **mt** = postnatal months

years numeric vector - age in years

L.ht numeric vector

M.ht numeric vector

S.ht numeric vector

L.wt numeric vector

M.wt numeric vector

S.wt numeric vector

L.bmi numeric vector

M.bmi numeric vector

S.bmi numeric vector

L.head numeric vector

M.head numeric vector

S.head numeric vector

origin two-level factor indicating the provenance of the data, with levels **British1990** and **WHO2006**

sex two-level factor with level 1 male and level 2 female

Details

The growth reference combines the birth section of the British 1990 growth reference (Cole et al 2011) from 26 to 42 weeks gestation, the WHO growth standard from 2 postnatal weeks to 4 years, and the British 1990 reference from 4 to 20 years.

Age is measured in years, where 40 weeks gestation is 0 years. The conversion from weeks gestation to years is: $\text{years} = (\text{weeks} - 40) * 7 / 365.25$.

The L, M and S values for each measurement correspond respectively to the Box-Cox power, median and coefficient of variation of the distribution by age and sex (Cole & Green 1992). The measurement short names and units (see [LMS2z](#)) are as follows: height (ht, cm), weight (wt, kg), BMI (bmi, kg/m²) and head circumference (head, cm).

Source

The values are tabulated in the Excel spreadsheet **UK_WHO_preterm.xls** provided with the Excel add-in **LMSGrowth** from <https://www.healthforallchildren.com/shop-base/software/lmsgrowth/>

References

- Cole TJ, Green PJ. Smoothing reference centile curves: the LMS method and penalized likelihood. *Stat Med* 1992;11:1305-19.
- Cole TJ, Williams AF, Wright CM, et al. Revised birth centiles for weight, length and head circumference in the UK-WHO growth charts. *Ann Hum Biol* 2011;38:7-11.
- Wright CM, Williams AF, Elliman D, et al. Using the new UK-WHO growth charts. *BMJ* 2010;340:c1140.

Examples

```
data(ukwhopt)
## calculate median birth weight (kg) in girls from 26 to 44 weeks gestation
v <- LMS2z(x = (26:44-40) * 7 / 365.25, y = 0, sex = 2, measure = 'wt',
  ref = 'ukwhopt', toz = FALSE)
setNames(v, 26:44)
```

ukwhoterm

UK-WHO growth reference omitting preterm data

Description

The UK-WHO growth reference for height, weight, BMI and head circumference (see Wright et al 2010), fitted by the LMS method and summarised by values of L, M and S by sex and postnatal age from term birth (see Details) to 20 years.

Usage

```
ukwhoterm
```

Format

A tibble with 512 observations on the following 15 variables:

years numeric vector - postnatal age in years

L.ht numeric vector

M.ht numeric vector

S.ht numeric vector

L.wt numeric vector

M.wt numeric vector

S.wt numeric vector

L.bmi numeric vector

M.bmi numeric vector

S.bmi numeric vector

L.head numeric vector

M.head numeric vector

S.head numeric vector

origin two-level factor indicating the provenance of the data, with levels British1990 and WHO2006

sex two-level factor with level 1 male and level 2 female

Details

The growth reference combines term birth data from the British 1990 growth reference (Cole et al 2011), the WHO growth standard from 2 postnatal weeks to 4 years, and the British 1990 reference from 4 to 20 years.

Age is measured in years, and term birth corresponds to ages between 37 and 42 weeks gestation, where 40 weeks gestation is 0 years. The conversion is: $\text{years} = (\text{weeks} - 40) * 7 / 365.25$.

The L, M and S values for each measurement correspond respectively to the Box-Cox power, median and coefficient of variation of the distribution by age and sex (Cole & Green 1992). The measurement short names and units (see [LMS2z](#)) are as follows: height (ht, cm), weight (wt, kg), BMI (bmi, kg/m2) and head circumference (head, cm).

Source

The values are tabulated in the Excel spreadsheet UK_WHO_preterm.xls provided with the Excel add-in LMSGrowth from <https://www.healthforallchildren.com/shop-base/software/lmsgrowth/>

References

Cole TJ, Green PJ. Smoothing reference centile curves: the LMS method and penalized likelihood. *Stat Med* 1992;11:1305-19.

Cole TJ, Williams AF, Wright CM, et al. Revised birth centiles for weight, length and head circumference in the UK-WHO growth charts. *Ann Hum Biol* 2011;38:7-11.

Wright CM, Williams AF, Elliman D, et al. Using the new UK-WHO growth charts. *BMJ* 2010;340:c1140.

Examples

```
data(ukwhoterm)
## calculate median weight (kg) in girls from 0 to 10 years
v <- LMS2z(x = 0:10, y = 0, sex = 2, measure = 'wt',
  ref = 'ukwhoterm', toz = FALSE)
setNames(v, 0:10)
```

velout

Identify outliers with abnormal velocity in growth curves

Description

Quickly identifies putative outliers in a large number of growth curves.

Usage

```
velout(x, y, id, data, lag = 1, velpower = 0.5, limit = 5, linearise = FALSE)
```

Arguments

<code>x</code>	age vector.
<code>y</code>	outcome vector, typically weight or height.
<code>id</code>	factor identifying each subject.
<code>data</code>	data frame containing <code>x</code> , <code>y</code> and <code>id</code> .
<code>lag</code>	lag between measurements for defining growth velocity.
<code>velpower</code>	a value, typically between 0 and 1, defining the power of Δx to use when calculating velocity as $\Delta y / \Delta x^{\text{velpower}}$. The default of 0.5 is midway between velocity and increment.
<code>limit</code>	the number of standard deviations beyond which a velocity is deemed to be an outlier.
<code>linearise</code>	if TRUE <code>y</code> is converted to a residual about the median curve of <code>y</code> versus <code>x</code> .

Details

The algorithm works by viewing serial measurements in each growth curve as triplets (A-B-C) and comparing the velocities between them. Velocity is calculated as

$$\text{diff}(y, \text{lag} = \text{lag}) / \text{diff}(x, \text{lag} = \text{lag})^{\text{velpower}}$$

Missing values for `x` or `y` are ignored. If any of the AB, BC or AC velocities are abnormal (more than `limit` SDs in absolute value from the median for the dataset) the code for B is non-zero.

Value

Returns a data frame with columns: `id`, `x`, `y` (from the call), `code` (as described below), `vel1`, `vel2` and `vel3` (corresponding to the velocities AB, BC and AC above). The 'data' attribute contains the name of 'data'.

`Code` is a factor taking values between 0 and 8, with 0 normal (see table below). Values 1-6 depend on the pattern of abnormal velocities, while 7 and 8 indicate a duplicate age (7 for the first in an individual and 8 for later ones). Edge outliers, i.e. first or last for an individual, have just one velocity. Code 4 indicates a conventional outlier, with both AB and BC abnormal and AC normal. Code 6 is an edge outlier. Other codes are not necessarily outliers, e.g. codes 1 or 3 may be adjacent to a code 4. Use `codeplot` to look at individual curves, and `zapvelout` to delete outliers.

code	AB+BC	AC	interpretation
0	0	0	no outlier
0	0	NA	no outlier
1	0	1	rare pattern
2	1	0	complicated - look at curve
3	1	1	adjacent to simple outlier
4	2	0	single outlier
5	2	1	double outlier
6	1	NA	edge outlier
7	-	-	first duplicate age
8	-	-	later duplicate age

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[codeplot](#), [zapvelout](#)

Examples

```
outliers <- velout(age, height, id, heights, limit=3)
```

who06

The WHO 2006 growth standard

Description

The WHO growth standard (WHO 2006) for height, weight, body mass index, circumferences and skinfold thicknesses, fitted by the LMS method and summarised by values of L, M and S by sex from birth to 5 years.

Usage

```
who06
```

Format

A tibble with 150 observations on the following 23 variables:

years age from 0 to 5 years

L.ht numeric vector

M.ht numeric vector

S.ht numeric vector

L.wt numeric vector

M.wt numeric vector

S.wt numeric vector

L.bmi numeric vector

M.bmi numeric vector

S.bmi numeric vector

L.head numeric vector

M.head numeric vector

S.head numeric vector

L.arm numeric vector

M.arm numeric vector
S.arm numeric vector
L.subscap numeric vector
M.subscap numeric vector
S.subscap numeric vector
L.tricep numeric vector
M.tricep numeric vector
S.tricep numeric vector
sex two-level factor with level 1 male and level 2 female

Details

The L, M and S values for each measurement correspond respectively to the Box-Cox power, median and coefficient of variation of the distribution by age and sex (Cole & Green 1992). The short names and units for each measurement (see [LMS2z](#)) are as follows: height (ht, cm), weight (wt, kg), body mass index (bmi, kg/m²), head circumference (head, cm), arm circumference (arm, cm), subscapular skinfold (subscap, mm), and tricep skinfold (tricep, mm).

Source

<https://www.who.int/toolkits/child-growth-standards>

References

World Health Organization. WHO Child Growth Standards: Methods and development: Length/height-for-age, weight-for-age, weight-for-length, weight-for-height and body mass index-for-age. Geneva: WHO; 2006.

Cole TJ, Green PJ. Smoothing reference centile curves: the LMS method and penalized likelihood. *Stat Med* 1992;11:1305-19.

Examples

```
data(who06)
## calculate z-score for length 60 cm in boys at age 0:12 months
LMS2z(x = 0:12/12, y = 60, sex = 1, measure = 'ht', ref = 'who06')
```

who0607

The WHO 2006 growth standard and WHO 2007 growth reference

Description

The WHO growth standard (WHO 2006) and growth reference (2007) for height, weight and body mass index, fitted by the LMS method and summarised by values of L, M and S by sex from birth to 19 years.

Usage

who0607

Format

A tibble with 486 observations on the following 11 variables:

years age from 0 to 19 years

L.ht numeric vector

M.ht numeric vector

S.ht numeric vector

L.wt numeric vector

M.wt numeric vector

S.wt numeric vector

L.bmi numeric vector

M.bmi numeric vector

S.bmi numeric vector

sex two-level factor with level 1 male and level 2 female

Details

The L, M and S values for each measurement correspond respectively to the Box-Cox power, median and coefficient of variation of the distribution by age and sex (Cole & Green 1992). The short names and units for each measurement (see [LMS2z](#)) are as follows: height (ht, cm), weight (wt, kg) and body mass index (bmi, kg/m²).

References

Cole TJ, Green PJ. Smoothing reference centile curves: the LMS method and penalized likelihood. *Stat Med* 1992;11:1305-19.

World Health Organization. WHO Child Growth Standards: Methods and development: Length/height-for-age, weight-for-age, weight-for-length, weight-for-height and body mass index-for-age. Geneva: WHO; 2006.

de Onis M, Onyango AW, Borghi E, Siyam A, Nishida C, Siekmann J. Development of a WHO growth reference for school-aged children and adolescents. *Bull WHO* 2007;85:660-7.

Examples

```
data(who0607)
## calculate 98th centile for BMI in girls from birth to 19 years
round(
  setNames(
    LMS2z(x = 0:19, y = 2, sex = 2, measure = 'bmi', ref = 'who0607',
      toz = FALSE), 0:19), 1)
```

xaxsd*Par args xaxs and yaxs option d*

Description

Implements par('xaxs') and par('yaxs') option 'd'.

Usage

```
xaxsd(usr = par()$usr[1:2])
```

```
yaxsd(usr = par()$usr[3:4])
```

Arguments

usr a length-2 vector defining the length of the x-axis or y-axis.

Details

Implements par('xaxs') and par('yaxs') option 'd', i.e. uses previous axis scales in a new plot.

Value

By default returns xlim/ylim args to match current setting of par()\$usr, i.e. previous plot scales. Specifying usr gives scales with the usr args at the extremes. If par('xlog') or par('ylog') are set the returned limits are antilogged (to base 10).

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
## generate and plot 100 data points
x <- rnorm(100)
y <- rnorm(100)
plot(x, y, pch=19)

## generate and plot 10 more
## constraining axis scales to be as before
x <- rnorm(10)
y <- rnorm(10)
plot(x, y, pch=19, xlim=xaxsd(), ylim=yaxsd())

## force axis extremes to be -3 and 3
plot(x, y, pch=19, xlim=xaxsd(c(-3,3)), ylim=yaxsd(c(-3,3)))
```

xyadj

*Adjust x and y variables for SITAR random effects***Description**

xyadj Adjusts x and y and optionally v values for subject-specific random effects from a SITAR model.

Usage

```
xyadj(object, x, y = 0, v = 0, id, abc = NULL, tomean = TRUE)
```

Arguments

object	a SITAR model.
x	a vector of x coordinates. If missing, x and y and id are obtained from object.
y	a vector of y coordinates (default 0).
v	a vector of velocity coordinates (default 0).
id	a factor denoting the subject levels corresponding to x and y and v.
abc	a data frame containing random effects for a, b, c and d (default ranef(object)[id,]).
tomean	a logical defining the direction of adjustment. TRUE (default) indicates that individual curves are translated and rotated to match the mean curve, while FALSE indicates the reverse, the mean curve being translated and rotated to match individual curves.

Details

When tomean = TRUE the x and y and v values are adjusted to

$$(x - xoffset - b < fixed > - b < random >) * \exp(c < random >) + xoffset + b < fixed >$$

$$y - a < random > - d < random > * x$$

$$(v - d < random >) / \exp(c < random >)$$

When tomean = FALSE they are adjusted to

$$(x - xoffset - b < fixed >) / \exp(c < random >) + xoffset + b < fixed > + b < random >$$

$$y + a < random > + d < random > * x$$

$$v * \exp(c < random >) + d < random >$$

In each case missing values of the fixed or random effects are set to zero.

Value

The list of adjusted values:

x	numeric vector.
y	numeric vector the same length as x, or NULL.
v	numeric vector the same length as x, or NULL.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

Examples

```
data(heights)
## fit sitar model for height
m1 <- sitar(x = age, y = height, id = id, data = heights, df = 5)

## plot unadjusted data as growth curves
plot(m1, opt='u')

## overplot with adjusted data as points
with(heights, points(xyadj(m1), col='red', pch = 19))
```

z2cent

Express z-scores as centile character strings for plotting

Description

Converts z-scores, typically defining centiles in a growth chart, to character strings that can be used to label the centile curves.

Usage

```
z2cent(z)
```

Arguments

z	a scalar or vector of z-scores.
---	---------------------------------

Value

A character string is returned, the same length as z. Z-scores between the 1st and 99th centile are converted to centiles with one or two significant figures (lower tail) or to their complement (upper tail). For larger z-scores in absolute value the character consists of "SDS" appended to the z-score rounded to one decimal place.

Author(s)

Tim Cole <tim.cole@ucl.ac.uk>

See Also

[cLMS](#)

Examples

```
z2cent(-4:4)
z2cent(qnorm(0:100/100))
```

Index

- * **aplot**
 - plot.sitar, 37
- * **arith**
 - cLMS, 12
 - LMS2z, 26
 - LMSfit, 28
 - pdLMS, 36
- * **character**
 - z2cent, 65
- * **datasets**
 - berkeley, 7
 - cdc2000, 10
 - deren, 14
 - heights, 22
 - iotf, 25
 - uk90, 54
 - ukwhopt, 55
 - ukwhoterm, 57
 - who06, 60
 - who0607, 61
- * **models**
 - sitar, 47
- * **nonlinear**
 - sitar, 47
- * **package**
 - sitar, 47
- * **regression**
 - BICadj, 8
 - bupdate, 10
 - sitar, 47
- addmargins, 17
- AIC, 9
- AICadj (BICadj), 8
- anova.lme, 5
- anova.sitar, 5
- aperm, 17
- apv_se, 6, 40
- berkeley, 7
- BIC, 9
- BICadj, 8
- bupdate, 10
- cdc2000, 10
- cLMS, 12, 27, 37, 66
- codeplot, 13, 60
- deren, 14
- dfpower, 15
- dfset, 17
- diffid (timegap), 52
- funcall, 18
- getCovariate.sitar (getData.sitar), 19
- getData.sitar, 19
- getDV, 19
- getL (BICadj), 8
- getPeak (getPeakTrough), 21
- getPeakTrough, 21
- getTakeoff (getPeakTrough), 21
- getTrough (getPeakTrough), 21
- getVarCov.sitar (getData.sitar), 19
- heights, 22
- ifun, 23, 40
- iotf, 25
- lines.sitar (plot.sitar), 37
- lmeObject, 52
- LMS2z, 11, 13, 25, 26, 29, 37, 55, 56, 58, 61, 62
- LMSfit, 28
- make.names, 49
- mplot, 29, 40
- n_agegp (optimal_design), 34
- nlme, 48
- nlmeObject, 49

ob_convertr, [30](#)
ob_convertr2(ob_convertr), [30](#)
optimal_design, [34](#)

par, [30](#), [36](#), [42](#)
pdLMS, [13](#), [36](#)
plot.sitar, [23](#), [24](#), [37](#)
plot_a(plot.sitar), [37](#)
plot_c(plot.sitar), [37](#)
plot_D(plot.sitar), [37](#)
plot_d(plot.sitar), [37](#)
plot_u(plot.sitar), [37](#)
plot_V(plot.sitar), [37](#)
plot_v(plot.sitar), [37](#)
plotclean, [40](#), [42](#)
predict.sitar, [43](#)
print.sitar, [44](#)
print.summary.sitar, [45](#)

recalib, [46](#)

sitar, [47](#), [51](#)
sitar-package, [3](#)
subsample, [48](#), [50](#)
subset, [48](#)
summary.lme, [51](#), [52](#)
summary.sitar, [51](#)

timegap, [52](#)

uk90, [54](#)
ukwhopt, [55](#)
ukwhoterm, [57](#)
update.sitar(sitar), [47](#)

varexp(BICadj), [8](#)
velout, [13](#), [14](#), [58](#)

who06, [60](#)
who0607, [61](#)

xaxsd, [63](#)
xyadj, [64](#)

yaxsd(xaxsd), [63](#)

z2cent, [13](#), [27](#), [29](#), [37](#), [65](#)
zapvelout, [60](#)
zapvelout(codeplot), [13](#)
zLMS, [27](#)
zLMS(cLMS), [12](#)